

LEASE NO: LC 031740B
LEASE NAME & WELL NO: MEYER B-8 #6
API #: 30-025-32213
COUNTY & STATE: LEA, NM

LINE 31: PERFORATION RECORD (INTERVAL, SIZE & NUMBER)
PERF LOWER 7 RVRS/QUEEN/PENROSE W/ 1 JSPF @ 3286, 3294, 3300,
3321, 3338, 3389, 3446, 3454, 3461, 3466, 3471, 3477, 3480, 3484,
3489, 3494, 3501, 3505, 3509, 3516, 3522, 3531, 3546, 3581, 3591,
3599, 3602, 3615, 3623, TOTAL OF 29 SHOTS.

PERF YATES & UPPER 7 RVRS W/ 1 JSPF @ 2864, 2868, 2883, 2887,
2890, 2965, 2981, 2985, 2990, 2995, 2999, 3004, 3009, 3014, 3018,
3025, 3086, 3100, 3108, 3111, 3117, 3127, 3131, 3137, 3147, 3153,
3172, 3180, TOTAL OF 28 HOLES.

LINE 32: ACID, SHOT, FRACTURE, CEMENT SQUEEZ3, ETC.

DEPTH INTERVAL

AMOUNT AND KIND OF MATERIAL USED

3286 - 3623

ACID W/ 2900g 7.5% NEFE HCL W/ MENTHANOL,
DIVERTED W/ 40 1.3 BALL SEALERS.
DISPLACED W/ 400g 50/50 METHANOL & 2%
KCL. FRAC W/ 30,000g 70 QUALITY CO2 FOAM
PAD, FOLLOWED W/ 30,000g 60 TO 50 QUALITY
FOAM, RAMPING 172,500# 12/20 OTTAWA 2-8#
SAND. FLUSH W/ 3300g FOAM.

2864 - 3180

ACID W/ 2300g 7.5% NEFE HCL W/ METHANOL,
DIVERTED W/ 38 1.3 BALL SEALERS, FLUSH W/
400g 50/50 METHONOL & 2% KCL FOLLOWED W/
700g KILL FLUID. FRAC W/ 40,000g 70
QUALITY CO2 FOAM PAD FOLLOWED W/ 40,000g
60 TO 50 QUALITY CO2 FOAM W/ 215,000#
12/20 OTTAWA SAND 2# TO 8#.