

**ATTACHMENT TO FORM 3160-3
APPLICATION FOR PERMIT TO DRILL**

Conoco Inc.

**Meyer B-8 No. 6
Sec. 8, T-21S, R-36E
Lea County, New Mexico**

1. The estimated tops of important geologic markers are shown on the attached Proposed Well Plan Outline.
2. The estimated depths at which anticipated water, oil, gas or other mineral-bearing formations to be encountered are shown on the attached Proposed Well Plan Outline.
3. A drawing of Blowout Preventer Specifications is attached. Pipe rams and blinds will be checked to the working pressure of the stack or 70% of the minimum internal yield strength of the casing whichever is less. BOP will be checked when casing string is set.
4. The proposed casing program is as follows:

0-420':	8-5/8"	24#	K-55
0-3800':	5-1/2"	15-1/2#	K-55
5. The proposed mud program is as follows:

0-420':	8.4# Fresh
420'-2700':	10.0-10.2 Brine
2700'-3800':	10.0-10.2 Brine w/starch
6. The logging suite will include the following open-hole logs:
1) GR-CAL-DLL-MSFL from 3800'-2600' and 2) GR-CAL-CNL-FDC from 3800'-2600'.
7. Special Drilling Problems:
 - a) Possible swelling in Red Beds
 - b) Possible salt section washout
 - c) Yates, 7-Rivers,s & Queen pressure depleted
8. The anticipated starting date is 9-1-93 with a duration of approximately 14 days.