

LEASE NO: LC 031740B
LEASE NAME & WELL NO: MEYER B-4 #30
API #: 30-025-32456
COUNTY & STATE: LEA, NM.

LINE 31: PERFORATION RECORD (INTERVAL, SIZE & NUMBER)

PERF QUEEN/PENROSE W/ 1 JSPF @ 3354, 3357, 3362, 3366, 3368, 3373, 3376, 3380, 3386, 3395, 3399, 3401, 3405, 3409, 3411, 3416, 3418, 3422, 3428, 3431, 3433, 3438, 3446, 3448, 3476, 3486, 3496, 3500, 3504, 3511, 3513, 3516, 3518, 3255, 3524 & 3526.

PERF YATES/7 RIVERS W/ 1 JSPF @ 2727, 2731, 3737, 3759, 3763, 2782, 2800, 2816, 2826, 2828, 2836, 2841, 2846, 2854, 2861, 2867, 2896, 2899, 2904, 2908, 2912, 2916, 2817, 2978, 2980, 2990, 2991, 2999, 3001, 3010, 3011, 3023, 3036, 3037, 3045, 3054, 3058, 3059, 3060 & 3061.

LINE 32: ACID, SHOT, FRACTURE, CEMENT SQUEEZ3, ETC.

DEPTH INTERVAL	AMOUNT AND KIND OF MATERIAL USED
3354 - 3526	ACID W/ 1000g 15% HCL, W/ METHANOL. SPEARHEADED FOLLOWED W/ 62,871g 60 QUALITY CO2 FOAM PAD, 62,876g 60-50 QUALITY CO2 FOAM, RAMPING 350,000# 12/20 BRADY SAND. FLUSH W/ 3100g CO2 FOAMED 7.5% HCL.
2727 - 3061	SPEARHEAD 1500g 15% HCL, METHANOL. FRAC W/ 48,000g 60 QUALITY CO2 FOAM PAD, 39,548g 60-50 QUALITY CO2 FOAM, RAMPING 234,000# 12-20 BRADY SAND. FLUSH W/ 2650g FOAM.