

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

U. OIL CONS. COMMISSION  
P.O. BOX 1980  
HOBBS, NEW MEXICO 88240

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Conoco Inc.

3. Address and Telephone No.

10 Desta Drive STE 100W, Midland, TX 79705 (915)686-5424

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FSL & 660' FWL, SEC. 17, T-21S, R-36E, UNIT LTR 'M'

5. Lease Designation and Serial No.

LC 031740A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

MEYER A-1 #21

9. API Well No.

30-025-32480

10. Field and Pool, or Exploratory Area

EUMONT VATES 7 RVRS QN

11. County or Parish, State

LEA, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other SPUD, SET SURFACE CSG  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4-7-94 MIRU SPUD 12 1/4" HOLE DRILL TO 441'. GIH W/ 11 JTS 8 5/8" 24# K-55 LT&C CSG SET @ 441'. SHOE SET @ 441' COLLAR SET @ 439'. LEAD SLURRY 225 SX CLASS 'C' W/ 4% GEL + 2% CACL. TAIL SLURRY 100 SX CLASS 'C' W/ 2% CACL. DISPLACED W/ 28 bbl FW. BUMPED PLUG @ 8:30 pm ON 4-7-94 W/ 850 PSI. NOTIFIED BLM @ 7:30 pm ON 4-7-94.  
4-8-94 CONTINUE DRILLING A 7 7/8" HOLE TO 3800'.

14. I hereby certify that the foregoing is true and correct

Signed Christ R. Kearley

Title SR. REGULATORY SPEC

Date 4-11-94

(This space for Federal or State office use)

Approved by \_\_\_\_\_

Title \_\_\_\_\_

Date \_\_\_\_\_

Conditions of approval, if any:

RECEIVED

MAY 01 1994

JUL HUBBS  
OFFICE