

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO. 30-025-33067
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. D 1115

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

State D

8. Well No.
20

9. Pool name or Wildcat
Eumont Yates 7 Rvrs. On (RG)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Conoco, Inc.

3. Address of Operator

10 Desta Drive, Suite 100W, Midland, Texas 79705

4. Well Location

Unit Letter I : 2180 Feet From The South Line and 910 Feet From The East Line

Section 15

Township 21S

Range 36E

NMPM Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3564' G.L.

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD-3720'. Ran 90 jts. 4 1/2" 11.60# K-55 casing to a total depth of 3720'. Float shoe on bottom and float collar one joint off bottom. Cemented with 750 sx Clas "C" Lite + 5 pps Salt + .2% SMS, followed by 350 sx Class "C" + 1.1% Flo-bloc + .2% SMS. Displaced with 58 bbls. 7 1/2% HCL + 2% KCL. Bumped plug at 10:15 pm on 9-12-95. Circulated 55 sx to pit. ND BOP, set slips, cut off casing, weld on head, and release rig at 3:00 am on 9-13-95.

I hereby certify that the information above is true and accurate to the best of my knowledge and belief.

SIGNATURE

TITLE

Regulatory
Agent

DATE 10/10/95

TYPE OR PRINT NAME

TELEPHONE NO

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

OCT 16 1995

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY.