

State of New Mexico
Energy, Minerals and Natural Resources Department

DISTRICT I

P.O. Box 1980, Hobbs NM 88240

DISTRICT II

P.O. Drawer DD, Artesia NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

| | |
|---|------------------------------|
| WELL API NO. | 30-025-33209 |
| 5. Indicate Type of Lease | |
| State <input checked="" type="checkbox"/> | FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No. | |
| V-3594 | |
| 7. Lease Name or Unit Agreement Name | |
| ALPHABET UNIT | |
| 8. Well No. | |
| 1 | |
| 9. Pool Name or Wildcat | |
| Grama Ridge Bone Springs, North | |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL ☐ GAS ☐
WELL ☒ WELL ☐ OTHER ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South 4th., Artesia, NM 88210

4. Well Location
Unit Letter C : 330 Feet From The NORTH Line and 1650 Feet From The WEST Line
Section 8 Township 21S Range 34E NMPM LEA COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3718' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-27-00- RU pulling unit. ND wellhead, NU BOP.

1-28-00- ND BOP. PU & RIH w/ stringer & 176 jts 2-7/8" tubing. Stung into CICR. Squeeze 60 sxs Class "C" Neat cement. Displace w/ 30 bbls fresh water. Dumped 15 sx cement on top. Squeeze w/ 1500 psi. Stung out of CICR. Laid down 2 jts. Reverse circ hole w/ mud-laden fluid. POH laying down 23 jts 2-7/8" tubing. SD for nite.

1-29-30-00- PUH to 1882', spot 50 sx Class "C" Neat cement @ 1882' to 1694'. PUH to 612'. Spot 50 sx Class C Neat cement. POH w/ tubing. WOC per OCD orders. All shoe plugs tagged. SD for nite.

2-1-00- Opened up well. RIH w/ tubing. ND BOP, RIH w/ 1 jt. Circ 20 sx Class C Neat at 31' to surface. POH w/ tubing. Rig down, move off. Install regulation dry hole marker.

I hereby certify that the information above a true and complete to the best of my knowledge and belief.

SIGNATURE

Donna Clack
DONNA CLACK

TITLE

Operations Technician

DATE

2/28/02

TYPE OR PRINT NAME

TELEPHONE NO.

505-748-1471

(This space for State Use)

APPROVED BY

[Signature]
ORIGINAL SIGNED BY *[Signature]*

DATE

3-12-02

CONDITIONS OF APPROVAL, IF ANY:

[Signature]