Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

M. Oil Cons. Div ion P.O. Box 1980 Hobbs, NM 88241 Budget Bu

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. NM-94853 6. If Indian, Allottee or Tribe Name Use "APPLICATION FOR PERMIT-" for such proposals SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ☐ Well X Wall Name of Operator 8. Well Name and No. Penwell Energy, Inc. J.D. "33" Federal #1 3. Address and Telephone No. 9. API Well No. 600 N. Marienfeld, Suite 1100, Midland, TX 79701, 915-683-2534 30-025-33488 4. Location of Well (Foolage, Sec., T., R., M., or Survey Description) 10. Field and Pool, or Exploratory Area 660' FNL & 2080' FEL, Sec. 33, T-12S, R-33E Legg-Atoka 11. County or Parish, State Lea County, New Mexico 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion Subsequent Report New Construction Plugging Back Non-Routine Fracturing Final Abandonment Notice Casing Repair ☐ Water Shut-Off Altering Casing Conversion to Injection Other Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinet details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markders and zones pertinent to this work.)\* TD=15,099'. Perfs @ 14,202'-211' - Squeezed w/50 sx., drilled out. Perfs @ 14,542'-548' & 14,509'-515', open & produced. Frac P&A Procedure: Set Plugs @: 1. 50' cmt. on top of BP @ 14,450'. 2. Cmt. plug. @ 12,055', 200' cmt. inside liner, 100' cmt. above liner. 3. 200' cmt. plug @ 10,055' - Tag. 4. 200' cmt. plug @ 8,055'. 5. 200' cmt, plug @ 6,053' 6. Cut & pull 3400' of 7" csg., 50' cmt. plug inside cut & 50' cmt. plug outside cut - Tag. 8. 100' cmt. plug @ 690'. 9. 100' cmt. plug @ 350'. 10. Cmt. plug @ 50', 50' cmt. plug to surface. regoing is true and correct Senior Production Engineer (This space for Federal or State office use) 04/06/98 Date (CRIG. SGD.) GARY GOURLEY Approved by \_\_\_(URRULE Conditions of approval, if any PETROLEUM ENGINEER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.