Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Divisior ≥0. Box 1980

Hobbs. NM 8824

FORM APPROVED adget Bureau No. 1004-0135

1980	Budget Bureau No. 1004-013
IM 8824	Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS	5. Lease Designation and Serial No.	
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.	NM-14331 6. If Indian, Alottee or Tribe Name	
Use "APPLICATION FOR PERMIT" for such proposals	or malan, motor of more name	
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation	
1. Type of Well: GAS COLUMN	8. Well Name and Number	
1. Type of Well: OIL GAS OTHER	BILBREY '30' FEDERAL	
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.	5	
3. Address and Telephone No. P.O. Box 2100, Denver Colorado 80201 (303)621-4851	9. API Well No. 30-025-33647	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	10. Field and Pool, Exploratory Area	
Unit Letter J : 1980 Feet From The SOUTH Line and 1980 Feet From The	LOST TANK DELAWARE	
7 male 04.0	11. County or Parish, State	
EAST Line Section 30 Township 21-S Range 32-E	LEA , NM	
Check Appropriate Box(s) To Indicate Nature of Notice, Re	eport, or Other Data	
	PE OF ACTION	
Abandonment	Change of Plans	
Recompletion	New Construction	
Notice of Intent	Non-Routine Fracturing	
Subsequent Report Casing Repair	Water Shut-Off	
Final Abandonment Notice ASS 3 1997 Altering Casing	Conversion to Injection	
OTHER: COMPLETION	Dispose Water	
	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)	
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones per	estimated date of starting any proposed work. If well is inent to this work,)*.	
 RU SCHLUMBERGER. RIH W/ BAKER WLS/TBG RET BP. CORRELATE F/DEPTH, SET PLU RIH W/ DUMP BAILER, DUMP 10' SAND ON PLUG. POH. RIH W/4" CSG GUNS. PERFORATI 6855'-6863', WITH 2 JSPF. 47 HOLES. 	G @ 7050'. TESTED PLUG 4000 PSI. E AS: FOLLOWS: 6797'-6806', 6819'-6822',	
2. RU DOWELL. ACIDIZED THE LOWER CHERRY CANYON W/900 GALS 7 1/2% NEFE HCL. F	RAC W/11,000 GALS 35# BORATE	
CROSSLINKED GEL AND 28,000 16/30 OTTAWA RCS. 03-08-97. 3. STRAP TBG IN HOLE TO 6970'. TOH. P/U MUD ANCHOR & SN. TIH W/223 JTS TBG, N/D BOP. SET TAC. NU WELLHEAD.		
SDFN. BTM OF MUD ANCHOR @ 6925', SN @ 6893'. 03-12-97.		
 RAN 2 1/2" X 1.75" X 20' PUMP, RODS, 03-13-97. MIRU YALE E. KEY W/S RIG. TOH W/ RODS & PUMP. 03-25-97. 		
 RU SCHLUMBERGER. RIH W/ BAKER RBP. SET PLUG @ 6700'. RAN GR/CCL STRIP LOG 4654'-4680' W/ 2 JSPF. 53 HOLES. RD SCHLUMBERGER. TIH W/SN & 147 JTS, 2-7/8" TBG 	F/5600'-4600'. PERFORATED AS FOLLOWS:	
7. RU DOWELL. ACIDIZED THE BELL CANYON W/2000 GALS 7-1/2% HCL NEFE. 03-27-97.	. LP:NDED 1BG @ 4352 : 03-20-97 :	
8. P/U 2-1/2" X 1-3/4" X 20' PUMP. RAN RODS. SN @ 4758'. 03-29-97. 9. OPT: PUMPED 123 BO, 149 BW, 18 MCF. 04-02-97.		
	er 21 7	
14. I hereby certify that the foregoing is true and correct SIGNATURE COLOR SISTEMATION FOR ASSISTANT	DATE 4/8/97	
SIGNATURE Sheilfa D. Reed-High	22 410/31	
(This space for Federal or State office use) APPROVED		
CONDITIONS OF APPROVAL, IF ANY:TITLE	DATE	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or

representations as to any matter within its jurisdiction