

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-025-34401
Indicate Type of Lease STATE ☒ FEE ☐
State Oil & Gas Lease No.
Lease Name or Unit Agreement Name STATE DC
Well No. 3
Pool name or Wildcat WANTZ (ABO)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	
Name of Operator TITAN RESOURCES I, INC.	
Address of Operator 500 W. TEXAS, STE 500; MIDLAND, TEXAS 79701	
Well Location Unit Letter F 1866 Feet From The N Line and 2195 Feet From The W Line Section 19 Township 21S Range 37E NMPM LEA County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 3511' GR	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: SPUD, SET CSG, CMT, (ACIDIZE), TBG, RODS, PRODUCE ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

SPUD WELL @ 9:00PM 5-25-98

5-25-98 RUN 8 5/8" 24# J-55 ST&C CSG & CMT W/ 420 SX 12.8 PPG PBCZ W/ 1/4# (YIELD 1.88) 10.26 GAL/SK.
TAIL W/ 135 SX 13.5 PPG PBCZ W/ 1/4# FLOCELE (YIELD 1.63) 8.37 GALS/SK.
6-08-98 RUN 5 1/2" 17# J-55 LT&C CSG & CMT W/ 618 SX 14.2 PPG 50/50 POZ 2% GEL, 5# SALT, 4/10% HALAD 9 (YIELD 1.33) 6.06 GALS/SK

2ND STAGE: 907 SX 11.9 PPG 1/4# FLOCELE INTER FILL C (YIELD 2.46) 14.28 GALS/SX

TAIL W/ 258 SX 14.2 PPG 50/50 POZ 2% GEL, 5# SALT, 4/10% HALAD 9 6.06 GALS/SK.

6-18-98 RUN GR/CCL/CBL 7775-3000'; TOC @ 2230'; PERF ABO 6887', 6942', 54', 61', 83', 7003', 50', 55', 69', 7109' 2 SPF SELECTFIRE (20 TOTAL HOLES).

6-19-98 ACIDIZE ABO (6887'-7002') 2500 GALS 15% NEFE; SPOT 250 GALS 15% ACID; PULL UP HOLE; SET PKR @ 6709'; LOAD BACKSIDE TO

500 PSI; ACIDIZE 2250 GALS 15% NEFE 40 BS.

6-25-98 ACIDIZE ABO 6887'-7109' W/ 10,000 GALS 20% GELLED ACID 30 QUALITY CO2.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Haylie Urias TITLE OPERATIONS TECH. DATE 08-03-98

TYPE OR PRINT NAME HAYLIE URIAS

TELEPHONE NO. 915-498-8661

(This space for State Use)

APPROVED BY [Signature] TITLE [Signature] DATE SEP 03 1998

CONDITIONS OF APPROVAL, IF ANY:

SEP 03 1998