

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL AP NO.

30-025-34424

5. Indicate Type of Lease

☒ STATE ☐ FEE

6. State Oil & Gas Lease No.

22503

7. Lease Name or Unit Agreement Name

Northeast Drinkard Unit

8. Well No.

124

9. Pool name or Wildcat

Eunice N. Blinebry-Tubb-Drinkard

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

☒ OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER

b. Type of Completion:

☒ New Well ☐ Workover ☐ Deepen ☐ Plug Back ☐ Diff. Resvr. ☐ Other

2. Name of Operator

Apache Corporation

3. Address of Operator

2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400 / 713-296-6000

4. Well Location

Unit Letter Lot 11 : 2879 Feet From The North Line and 2650 Feet From The East Line
Section 3 Township 21S Range 37E NMPM Lea County

10. Date Spudded

10/31/98

11. Date T.D. Reached

11/12/98

12. Date Compl. (Ready to Prod.)

12/04/98

13. Elevations (DF& RKB, RT, GR, etc.)

3478'

GR

14. Elev. Casinghead

15. Total Depth

6910

16. Plug Back T.D.

6830

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools

Cable Tools

X

19. Producing Interval(s), of this completion - Top, Bottom, Name

Blinebry 5586 - 5888 Tubb 6168 - 6372 Drinkard 6647 - 6768

20. Was Directional Survey Made

NO

21. Type Electric and Other Logs Run

GR-CNL / CBL

22. Was Well Cored

NO

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB. / FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	1309	11"	410 sx / Circulated 76 sx	
5-1/2"	17#	6910	7-7/8"	1425 sx / Circulated 86 sx	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2 7/8	6791	

26. Perforation record (interval, size, and number)

Blinebry 5586-92, 5696-5700, 06-10, 16-32, 36-40, 82-97, 5801-10, 58-80, 83-88 - 4" - 604 Holes

Tubb 6168-72, 87-97, 6301-11, 19-36, 57-72 - 4" - 224 Holes

Drinkard 6647-76, 83-96, 6718-32, 38-68 - 4" - 344 Holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
5586 - 5888	Acidize w / 5000 gals 15% BxDx
	Frac w / 32250 gals gel / 70650# 16/30 sand
6168 - 6372	Acidize w / 2848 gals 15% HCL
	Frac w / 25668 gals gel / 70000# 16/30 sand
6647 - 6768	Acidize w / 4572 gals 15% HCL
	Frac w / 12500 gals gel / 35000# 16/30 sand

28. PRODUCTION

Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)				Well Status (Prod. or Shut-in)	
12/4/98		Pumping - 1.5" Rod Insert				Producing	
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl.	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
12/8/98	24			72	254	240	3527
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	
							37.4

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold

Test Witnessed By

Apache Corporation

30. List Attachments

Log

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature

Printed Name

Debra J. Anderson

Title

Engineering Tech.

Date

12/21/98

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	_____
T. Salt	_____
B. Salt	_____
T. Yates	2630
T. 7 Rivers	_____
T. Queen	_____
T. Grayburg	_____
T. San Andres	3704
T. Glorieta	5236
T. Paddock	5302
T. Blinebry	5664
T. Tubb	6200
T. Drinkard	6538
T. Abo	6844
T. Wolfcamp	_____
T. Penn	_____
T. Cisco (Bough C)	_____

Northwestern New Mexico

T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Miss	T. Cliff House	T. Leadville
T. Devonian	T. Menefee	T. Madison
T. Silurian	T. Point Lookout	T. Elbert
T. Montoya	T. Mancos	T. McCracken
T. Simpson	T. Gallup	T. Ignacio Otzte
T. McKee	Base Greenhorn	T. Granite
T. Ellenburger	T. Dakota	T. _____
T. Gr. Wash	T. Morrison	T. _____
T. Delaware Sand	T. Todilto	T. _____
T. Bone Springs	T. Entrada	T. _____
T. Rustler	1317 T. Wingate	T. _____
T. _____	T. Chinle	T. _____
T. _____	T. Permian	T. _____
T. _____	T. Penn "A"	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet _____

No. 2, from _____ to _____ feet _____

No. 3, from _____ to _____ feet _____

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology