

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-34429

5. Indicate Type of Lease

☒ STATE ☐ FEE

6. State Oil & Gas Lease No.

22503

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

☒ OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER

b. Type of Completion:

☒ New Well ☐ Workover ☐ Deepen ☐ Plug Back ☐ Diff. Resvr. ☐ Other

2. Name of Operator

Apache Corporation

3. Address of Operator

2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400

4. Well Location

Unit Letter Lot 10 : 3730 Feet From The North Line and 2594 Feet From The East Line
Section 3 Township 21S Range 37E NMPM Lea County

10. Date Spudded

11/01/98

11. Date T.D. Reached

11/13/98

12. Date Compl. (Ready to Prod.)

12/02/98

13. Elevations (DF & RKB, RT, GR, etc.)

3472'

GR

14. Elev. Casinghead

15. Total Depth

6910

16. Plug Back T.D.

6856

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools

Cable Tools

X

19. Producing Interval(s), of this completion - Top, Bottom, Name

Blinebry 5663 - 5906 Tubb 6161 - 6400 Drinkard 6537 - 6770

20. Was Directional Survey Made

NO

21. Type Electric and Other Logs Run

GR-CNL / GR-AZL / CBL

22. Was Well Cored

NO

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	1309	11"	410 sx / Circulated 126 sx	
5-1/2"	17#	6910	7-7/8"	1325 sx / Circulated 170 sx	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2-7/8"	6800	

26. Perforation record (interval, size, and number)

Blinebry 5663-70, 79-92, 98-5724, 57-60, 65-80, 84-90, 5842-66,
92-5906 - 4" - 432 Holes

Tubb 6161-66, 78-88, 6203-10, 34-44, 50-52, 56-59, 6304-18, 22-30,
66-76, 95-6400 - 4" - 296 Holes

Drinkard 6537-46, 64-6602, 67-75, 6732-51, 62-70 - 4" - 328 Holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
5663 - 5906	Acidize w / 5500 gals 15% BxDx
	Frac w / 31400 gals gel / 70000# 16/30 sand
6161 - 6400	Acidize w / 4000 gals 15% BxDx
	Frac w / 32000 gals gel / 70500# 16/30 sand
6537 - 6770	Acidize w / 3642 gals 15% HCL
	Frac w / 12932 gals gel / 34190# 16/30 sand

28. PRODUCTION

Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)				Well Status (Prod. or Shut-in)	
12/02/98		Pumping - 1.5" Rod Insert				Producing	
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl.	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
12/12/98	24			45	221	222	4911
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	
							37.4

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold

Test Witnessed By


Apache Corporation

30. List Attachments

Log

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature



Printed Name

Debra J. Anderson

Title

Engineering Tech.

Date

12/21/98

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy		T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Salt		T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
B. Salt		T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Yates	2604	T. Miss		T. Cliff House		T. Leadville	
T. 7 Rivers		T. Devonian		T. Menefee		T. Madison	
T. Queen		T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Mancos		T. McCracken	
T. San Andres	3764	T. Simpson		T. Gallup		T. Ignacio Otzte	
T. Glorieta	5220	T. McKee		Base Greenhorn		T. Granite	
T. Paddock	5282	T. Ellenburger		T. Dakota		T.	
T. Blinebry	5644	T. Gr. Wash		T. Morrison		T.	
T. Tubb	6196	T. Delaware Sand		T. Todilto		T.	
T. Drinkard	6553	T. Bone Springs		T. Entrada		T.	
T. Abo	6836	T. Rustler	1303	T. Wingate		T.	
T. Wolfcamp		T.		T. Chinle		T.	
T. Penn		T.		T. Permain		T.	
T. Cisco (Bough C)		T.		T. Penn "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____

No. 2, from _____ to _____

No. 3, from _____ to _____

No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet _____

No. 2, from _____ to _____ feet _____

No. 3, from _____ to _____ feet _____

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology