

DISTRICT I

1625 N. French Dr., Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-34595

5. Indicate Type of Lease

☒ STATE☐ FEE

6. State Oil & Gas Lease No.

22503

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

☒ OIL WELL☐ GAS WELL☐ DRY☐ OTHER

b. Type of Completion:

☒ New Well☐ Workover☐ Deepen☐ Plug Back☐ Diff. Resvr.☐ Other

7. Lease Name or Unit Agreement Name

Northeast Drinkard Unit

2. Name of Operator

Apache Corporation

8. Well No.

924

3. Address of Operator

2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400

9. Pool name or Wildcat

Eunice N., Blinebry-Tubb-Drinkard

4. Well Location

Unit Letter **M** **1065** Feet From The **South** Line and **130** Feet From The **West** Line
 Section **23** Township **21S** Range **37E** NMPM **Lea** County

10. Date Spudded

04/24/99

11. Date T.D. Reached

05/06/99

12. Date Compl. (Ready to Prod.)

05/25/99

13. Elevations (DF & RKB, RT, GR, etc.)

3399'

14. Elev. Casinghead

GR

15. Total Depth

6722

16. Plug Back T.D.

6680

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools

Cable Tools

X

19. Producing Interval(s), of this completion - Top, Bottom, Name

Blinebry 5444 - 5732 Tubb 5870 - 6206 Drinkard 6336 - 6606

20. Was Directional Survey Made

NO

21. Type Electric and Other Logs Run

GR-CNL / GR-DLL

22. Was Well Cored

NO

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB. / FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	1210	11"	380 sx / Circulated 122 sx	
5-1/2"	17#	6722	7-7/8"	1300 sx / Circulated 43 sx	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2-7/8"	6614	

26. Perforation record (interval, size, and number)

Blinebry 5444-59, 80-86, 93-98, 5508-48, 54-64, 94-5636, 56-96, 5700-08, 16-20, 24-32 - 4" - 712 Holes

Tubb 5870-96, 5946-80, 86-6006, 24-34, 6116-28, 34-68, 72-90, 6202-06 - 4" - 362 Holes

Drinkard 6336, 50, 60, 72, 86, 91, 97, 6406, 15, 19, 6444-6510, 6514-20, 24-40, 46-84, 6590-6606 - 4" - 216 Holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
5444 - 5732	Acidize w / 7000 gals 15% HCL
	Frac w / 28,186 gals gel & 132,000# 16/30 sand
5870 - 6206	Acidize w / 7000 gals 15% HCL
	Frac w / 46,200 gals gel & 76,880# 16/30 sand
6336 - 6606	Acidize w / 6199 gals 15% HCL
	Frac w / 26,394 gals gel & 60,480# 16/30 sand

28. PRODUCTION

Date First Production 05/27/99	Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping - 1.5" Rod Insert				Well Status (Prod. or Shut-in) Producing	
Date of Test 06/06/99	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl. 50	Gas - MCF 679	Water - Bbl. 18
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.) 38.2

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold

Test Witnessed By

Apache Corporation

30. List Attachments

Logs

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature

Printed Name

Debra J. Anderson

Title

Sr. Engr. Tech.

Date

06/10/99

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy		T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Salt		T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
B. Salt		T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Yates	2514	T. Miss		T. Cliff House		T. Leadville	
T. 7 Rivers		T. Devonian		T. Menefee		T. Madison	
T. Queen		T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Mancos		T. McCracken	
T. San Andres	3650	T. Simpson		T. Gallup		T. Ignacio Otzte	
T. Glorieta	5066	T. McKee		Base Greenhorn		T. Granite	
T. Paddock	5137	T. Ellenburger		T. Dakota		T.	
T. Blinebry	5478	T. Gr. Wash		T. Morrison		T.	
T. Tubb	6011	T. Delaware Sand		T. Todilto		T.	
T. Drinkard	6346	T. Bone Springs		T. Entrada		T.	
T. Abo	6647	T. Rustler	1205	T. Wingate		T.	
T. Wolfcamp		T.		T. Chinle		T.	
T. Penn		T.		T. Permian		T.	
T. Cisco (Bough C)		T.		T. Penn "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet

No. 2, from to feet

No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology