Submit 3 Copies	State of New		Form C-103	
to Appropriate	Energy, Minerals and Natura	al Resources Department	Revised 1-1-89	
District Office				
DISTRICT I	OIL CONSERVAT	TION DIVISION	WELL API NO.	
1625 N. French Dr., Hobbs, NM 88240	P.O. Box	2088	30-025-34649	
DISTRICT II	Santa Fe, New Mexico 87504-2088		5. Indicate Type of Lease	
P.O. Drawer DD, Artesia, NM 88210			STATE FEE	
DISTRICT III			6. State Oil & Gas Lease No.	
1000 Rio Brazos Rd., Aztec, NM 87410			22503	
SUNDRY NOTICES AND REPORTS ON WELLS				
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"			7. Lease Name or Unit Agreement Name	
(FORM C-101) FOR SUCH PROPOSALS.)			Northeast Drinkard Unit	
1. Type of Well:				
🖸 OIL WELL	GAS WELL OTHER			
2. Name of Operator			8. Well No.	
Apache Corporation 3. Address of Operator			622	
			9. Pool name or Wildcat	
4. Well Location	. 100, Houston, Texas 77056-	4400	Eunice N., Blinebry-Tubb-Drinkard	
Unit Letter C	: 1229 Feet From The NO	rth Line and 2498	Feet From The West Line	
Section 15	Township 21S Range	37Е ммрм		
	10. Elevation (Show whether 3442' GR	er DF, RKB, RT, GR, etc.)		
		Dov to Indiante Mature of Matie	Depend on Others Date	
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
Perform Remedial Work	Plug and Abandon	Remedial Work	Altering Casing	
Temporarily Abandon	Change Plans	Commence Drilling Operations Drug and Abandonment		
Pull or Alter Casing		Casing Test and Cement Job		
Other		✓ Other	Surface & Production Casing	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/16/99 MIRU Patterson Rig # 63. Spud well @ 4:30 pm

8/17/99 Drilled 12-1/4" hole to 1265'. Ran 30 jts 8-5/8" 24# K-55 ST&C casing. Cemented w / 460sx Class "C". Circulated 107 sx to pit.

 8/29/99
 Drilled 7-7/8" hole to 6840'. Ran 166 jts 5-1/2" 17# J-55 LT&C casing. Cemented w / 1125 sx

 35/65 POZ "C" and 550 sx 50/50 POZ "H". Cement did not circulate. TOC @ 650' (CBL)

 Top of float collar @ 6757'. Top of float shoe @ 6838'. Rig released @ 8:15 AM

I hereby certify that the information above is true and complete to the best of my knowledge and	belief		
	Sr. Engineering Technician	DATE	8/31/99
TYPE OR PRINT NAME Debra H Anderson		TELEPHONE NO.	713-296-6338
(This space for State Use) (This space for State Use) (APPROVED BY ORIGINAL SIGNED BY CHRIS WILLIAMS (APPROVED BY DISTRICT I SUPERVISOR TITLE		DATESEE	1 5 399
CONDITIONS OF APPROVAL, IF ANY:			

