÷					
Submil 3 Copies	State of New Mexico		Form C-103		
to Appropriate	Energy, Minerals and Natural Resources Department		Revised 1-1-89		
District Office					
DISTRICT I	OIL CONSERVATION DIVISION		WELL API NO.		
1625 N. French Dr., Hobbs, NM 88240	P.O. Box 2088		30-025-34651		
DISTRICT II	Santa Fe, New Mexico 87504-2088		5. Indicate Type of Lease		
P.O. Drawer DD, Artesia, NM 88210			STATE 📝 FEE		
DISTRICT III		6. State Oil & Gas Lease No.			
1000 Rio Brazos Rd., Azlec, NM 87410		22503			
SUNDRY NOTICES AND REPORTS ON WELLS					
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"					
(FORM C-101) FOR SUCH PROPOSALS.)			Northeast Drinkard Unit		
1. Type of Well:					
	GAS WELL OTHER				
2. Name of Operator			8. Well No.		
Apache Corporation			128		
			9. Pool name or Wildcat		
2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400			Eunice N., Blinebry-Tubb-Drinkard		
Unit Letter Lot 5 : 2483 Feet From The North Line and 1277 Feet From The West Line					
Section 3	Township 21S Range	37E NMPM	Lea County		
10. Elevation (Show whether DF, RKB, RT, GR, etc.)					
3476' GR					
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data					
			SEQUENT REPORT OF:		
Perform Remedial Work	Plug and Abandon	Remedial Work	Altering Casing		
Temporarily Abandon	Change Plans	Commence Drilling Operations			
Pull or Alter Casing					
		Casing Test and Cement Job			
Other		✓ Other	Surface & Production Casing		

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/25/99 MIRU Patterson Rig # 65. Spud well @ 5:00 pm

7/26/99 Drilled 12-1/4" hole to 1336'. Ran 32 jts 8-5/8" 24# K-55 ST&C casing. Cemented w / 460 sx Class "C". Circulated 100 sx to pit.

8/8/99 Drilled 7-7/8" hole to 6930'. Ran 168 jts 5-1/2" 17# J-55 LT&C casing. Cemented w / 1000 sx 35/65 POZ "C" & 500 sx 50/50 POZ "H". Circulated 129 sx to pit. Top of float collar @ 6851'. Top of float shoe @ 6928'. Rig released @ 3:00 pm

I hereby certify that the information above is frue and complete to the best of my knowledge. SIGNATURE	and belief. Sr. Engineering Technician	DATE	8/9/99
TYPE OR PRINT MAME Debra Anderson		TELEPHO	DNE NO.
(This space for State Use) APPROVED BY <u>GARY WINK</u> TITLE CONDITIONS OF APPROVAL, FIE LD REP. 11		DATE	8-12-99