Submit 3 Copies	State of New	w Mexico	Form C-103		
lo Appropriate	Energy, Minerals and Natura	al Resources Department	Revised 1-1-89		
District Office					
DISTRICT I	OIL CONSERVATION DIVISION		WELL API NO.		
1625 N. French Dr., Hobbs, NM 88240	P.O. Box 2088		30-025-34655		
DISTRICT II	Santa Fe, New Mexico 87504-2088		5. Indicate Type of Lease		
P.O. Drawer DD, Artesia, NM 88210			STATE FEE		
DISTRICT III			6. State Oil & Gas Lease No.		
1000 Rio Brazos Rd., Aztec, NM 87410		22503			
SUNDRY NOTICES AND REPORTS ON WELLS					
	OR PROPOSALS TO DRILL OR TO I RESERVOIR. USE "APPLICATION	7. Lease Name or Unit Agreement Name			
(FORM C-101) FOR SUCH PROPOSALS.)			Northeast Drinkard Unit		
1. Type of Well:					
	GAS WELL OTHER				
2. Name of Operator			8. Well No.		
Apache Corporation		926			
3. Address of Operator			9. Pool name or Wildcat Eunice N., Blinebry-Tubb-Drinkard		
2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400			Lunce N., Binebry-Tubb-Dinkaru		
Unit Letter N	: 1172 Feet From The SO	uth Line and 2424	Feet From The West Line		
Section 23	Township 21S Range	37E NMPM	Lea County		
10. Elevation (Show whether DF, RKB, RT, GR, etc.)					
3383 GR					
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data					
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
Perform Remedial Work	Plug and Abandon	Remedial Work	Altering Casing		
Temporarily Abandon	Change Plans	Commence Drilling Operations 🗌 Plug and Abandonment			
Pull or Alter Casing	or Alter Casing Test and Cement Job				
Other		Other Surface & Production Casing			

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/17/99 MIRU Patterson Rig # 63. Spud well @ 2:30 pm

;

5

- 7/18/99 Drilled 12-1/4" hole to 1245'. Ran 31 jts 8-5/8" 24# K-55 ST&C casing. Cemented w / 460 sx Class "C". Circulated 88 sx to pit.
- 7/31/99 Drilled 7-7/8" hole to 6840'. Ran 165 jts 5-1/2" 17# J-55 LT&C casing. Cemented w / 875 sx 35/65 POZ "C" & 525 sx 50/50 POZ "H". Circulated 26 sx to pit. Top of float collar @ 6754'. Top of float shoe @ 6838'. Rig released @ 7:00 pm.

I hereby certify that the information above is true and complete to the best of my knowledge an SIGNATURE	^{id belief.} Sr. Engineering Technician	DATE	8/2/99
TYPE OR PRINT NAME Debra J. Anderson		TELEPHONE NO.	713-296-6338
(This space for State Use) GINAL SIGNED BY CERTURY		Λi	JG 1 8 1999
APPROVED BY DISTRICT I SUPERVISOF TITLE		DATE	10 1999
CONDITIONS OF APPROVAL, IF ANY:			

V