Submit 3 Copies	State of Nev	w Mexico		Form C-103		
to Appropriate	Energy, Minerals and Natura	al Resources Department		Revised 1-1-89		
District Office						
DISTRICT I	OIL CONSERVATION DIVISION		WELL API NO.			
1625 N. French Dr., Hobbs, NM 88240	P.O. Box 2088		30-025-34656			
DISTRICT II	Santa Fe, New Mexico 87504-2088		5. Indicate Type of Lease			
P.O. Drawer DD, Artesia, NM 88210			STATE	FEE		
DISTRICT III			6. State Oil & Gas Lease No.			
1000 Rio Brazos Rd., Aztec, NM 87410			22503			
SUNDRY	NOTICES AND REPORTS C	N WELLS				
(DO NOT USE THIS FORM F	OR PROPOSALS TO DRILL OR TO D	7. Lease Name or Unit Agreement Nam	e			
·	RESERVOIR. USE "APPLICATION F					
(F	ORM C-101) FOR SUCH PROPOSAL	_S.)	Northeast Drinkard Unit			
1. Type of Well:			1			
OIL WELL	GAS WELL OTHER					
2. Name of Operator			8. Well No.			
Apache Corporation			618			
3. Address of Operator			9. Pool name or Wildcat			
2000 POST OAK BIVG., STE 4. Well Location	e. 100, Houston, Texas 77056	Eunice N., Blinebry-Tubb-Drinkard				
Unit Letter B	: 1290 Feet From The NO	rth Line and 1330	Feet From The East Line	9		
Section 15	Township 21S Bange	37Е ММРМ	Lea County			
	10. Elevation (Show wheth 3442' GR		Lou oouny			
11 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data						
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:						
Perform Remedial Work	Plug and Abandon	Remedial Work	Altering Ca	asing		
Temporarily Abandon Change Plans		Commence Dril	ling Operations 🛛 🔲 Plug and A	bandonment		
Pull or Alter Casing	Casing Test and Cement Job					
Other		✓ Other	Surface & Production Casing			
12. Describe Proposed or Completed Op SEE RULE 1103.	erations (Clearly state all pertinent details, and giv	e pertinent dates, including estimated date	of starting any proposed work)			

9/9/99	MIRU Patterson Rig # 65. Spud well @ 6:30 pm
9/10/99	Drilled 12-1/4" hole to 1254'. Ran 30 jts 8-5/8" 24# K-55 ST&C casing. Cemented w / 460 sx Class "C". Circulated 110 sx to pit
9/22/99	Drilled 7-7/8" hole to 6820'. Ran 165 jts 5-1/2" 17# J-55 LT&C casing. Cemented w / 1025 sx 65/35 POZ "C" & 500 sx 50/50 POZ "H". Circulated 100 sx to pit. Top of float collar @ 6733'. Top of float shoe @ 6818'. Rig released @ 5:00 am

	0			
I hereby certify that the infol	rmation above is true and complete to the best of my knowledge and t	belief.		
	DOL MADAMATILE	Sr. Engineering Technician	DATE	9/23/99
TYPE OR PRINT NAME	Debra J. Anderson		TELEPHONE	NO
(This space for State Use)	ORIGINAL SIGNED BY CHRIS WILLIAMS			
APPROVED BY	DISTRICT I SUPERVISORE		DATE	EP 2 8 1603
CONDITIONS OF APPROV	AL, IF ANY:			



-