	State of New	Mexico	Form C-103			
Submit 3 Copies	Energy, Minerals and Natura		Revised 1-1-89			
to Appropriate District Office	Energy, Minoralo and Hatara					
	OIL CONSERVAT	ION DIVISION	WELL API NO.			
DISTRICT I	P.O. Box 2088		30-025-34660			
1625 N. French Dr., Hobbs, NM 88240	Santa Fe, New Mexico 87504-2088		5. Indicate Type of Lease			
DISTRICT II	Santa Fe, New Mexico 07504-2000		STATE STATE			
P.O. Drawer DD. Artesia, NM 88210			6. State Oil & Gas Lease No.			
DISTRICT III			22503			
1000 Rio Brazos Rd., Aztec, NM 87410		22000				
	NOTICES AND REPORTS O	7. Lease Name or Unit Agreement Name				
I (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR FLOG DAOR TO A						
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"			Northeast Drinkard Unit			
(FORM C-101) FOR SUCH PROPOSALS.)						
1. Type of Well:						
OIL WELL	GAS WELL OTHER					
2. Name of Operator			8, Well No.			
Apache Corporation			716			
3. Address of Operator			9. Pool name or Wildcat			
2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400			Eunice N., Blinebry-Tubb-Drinkard			
4 Well Location			Feet From The West Line			
Unit Letter D	. 61 Feet From The NO					
Section 22	Township 21S Range	37E NMPN	A Lea County			
	10. Elevation (Show wheth 3428 GR	er DF, RKB, RT, GR, etc.)				
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data						
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:						
NOTICE OF						
Perform Remedial Work	Plug and Abandon	Remedial Work Altering Casing				
Temporarily Abandon	andon Change Plans Commence Dri		illing Operations 🗌 Plug and Abandonment			
Pull or Alter Casing		Casing Test and Cement Job				
Other		Surface & Production Casing				
		- antianat datas, including estimated data	of stading any proposed work)			

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 8/1/99 MIRU Patterson Rig # 63. Spud well @ 1:45 pm
- 8/2/99 Drilled 12-1/4" hole to 1269'. Ran 30 jts 8-5/8" 24# K-55 ST&C casing. Cemented w / 460 sx Class "C". Circulated 92 sx to pit

8/15/99 Drilled 7-7/8" hole to 6810'. Ran 165 jts 5-1/2" 17# K&J-55 LT&C casing. Cemented w / 1075 sx 35/65 POZ "C" & 475 sx 50/50 POZ "H". Circulated 20 sx to pit. Top of float collar @ 6727'. Top of float shoe @ 6808' Rig released @ 10:00 pm

I hereby certify the information above is true and complete to the best of my knowledges SIGNATURE	^{ge and belief.} Sr. Engineering Technician	DATE	8/17/99
TYPE OR PRINT HAME DEDra J. Anderson		TELEPHONE NO.	713-296-6338
(This space for State Use) ORIGINAL SIGNED BY CHRIS WILLIAUTHE		DATE	AUG 26 1999.
CONDITIONS OF APPROVAL, IF ANY:			