

DISTRICT I

1625 N. French Dr., Hobbs, NM 88240

DISTRICT II

811 South First, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-105

Revised March 25, 1999

WELL API NO. 30-025-34738
5. Indicate Type of Lease ☐ STATE ☒ FEE
6. State Oil & Gas Lease No. 22503

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: ☒ OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER		7. Lease Name or Unit Agreement Name Northeast Drinkard Unit	
b. Type of Completion: ☒ New Well ☐ Workover ☐ Deepen ☐ Plug Back ☐ Diff. Resvr. ☐ Other			
2. Name of Operator Apache Corporation		8. Well No. 234	
3. Address of Operator 2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400		9. Pool name or Wildcat Eunice N., Blinebry-Tubb-Drinkard	
4. Well Location Unit Letter Lot 16 : 3810 Feet From The South Line and 200 Feet From The East Line Section 4 Township 21S Range 37E NMPM Lea County			
10. Date Spudded 01/03/00	11. Date T.D. Reached 01/16/00	12. Date Compl. (Ready to Prod.) 02/11/00	13. Elevations (DF & RKB, RT, GR, etc.) 3431' GR
14. Elev. Casinghead			
15. Total Depth 6900	16. Plug Back T.D. 6811	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By X
19. Producing Interval(s), of this completion - Top, Bottom, Name Blinebry 5623 - 5850 Tubb 6170 - 6392 Drinkard 6571 - 6692			20. Was Directional Survey Made NO
21. Type Electric and Other Logs Run GR-CNL / GR-AZL			22. Was Well Cored NO

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8	24#	1275	12-1/4	460 sx / Circulate 82 sx	
5-1/2	17#	6900	7-7/8	1740 sx / Circulate 150 sx	

24. LINER RECORD				25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET
					2-7/8	6752

26. Perforation record (interval, size, and number) Blinebry 5623-27, 41-45, 49-53, 56-70, 75-5704 - 4" - 373 Holes Tubb 6170-82, 92-6204, 07-12, 88-92, 98-6302, 09-18, 50-67, 78-82, 87-92 - 4" - 297 Holes Drinkard 6571-76, 6634-39, 68-79, 82-92 - 4" - 128 Holes		27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 5623 - 5704 Acidize w / 6300 gals 15% HCL Frac w / 21420 gals gel & 80000# 16/30 sand 6170 - 6392 Acidize w / 4500 gals 15% BxDx Frac w / 17500 gals gel & 64860# 16/30 sand 6571 - 6692 Acidize w / 1900 gals 15% HCL Frac w / 19000 gals gel & 20600# 16/30 sand	
--	--	--	--

28. PRODUCTION							
Date First Production 02/12/00		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping - 1.5" Rod Insert				Well Status (Prod. or Shut-in) Producing	
Date of Test 2/13/00	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl. 101	Gas - MCF 120	Water - Bbl. 102	Gas - Oil Ratio 1188
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.) 38.6	

29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold	Test Witnessed By Apache Corporation
---	--

30. List Attachments Logs, Deviation Report, C-104
--

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief			
Signature 	Printed Name Debra J. Anderson	Title Sr. Engr. Tech.	Date 2/15/00

JC

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division Office not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy		T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Salt		T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
B. Salt		T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Yates	2572	T. Miss		T. Cliff House		T. Leadville	
T. 7 Rivers		T. Devonian		T. Menefee		T. Madison	
T. Queen		T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Mancos		T. McCracken	
T. San Andres	3690	T. Simpson		T. Gallup		T. Ignacio Otzte	
T. Glorieta	5176	T. McKee		Base Greenhorn		T. Granite	
T. Paddock	5246	T. Ellenburger		T. Dakota		T.	
T. Blinebry	5648	T. Gr. Wash		T. Morrison		T.	
T. Tubb	6183	T. Delaware Sand		T. Todilto		T.	
T. Drinkard	6532	T. Bone Springs		T. Entrada		T.	
T. Abo	6814	T. Rustler	1258	T. Wingate		T.	
T. Wolfcamp		T.		T. Chinle		T.	
T. Penn		T.		T. Permian		T.	
T. Cisco (Bough C)		T.		T. Penn "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from to No. 3, from to
No. 2, from to No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet
 No. 2, from to feet
 No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology

100-443886-100