Submit 3 Copies to Approriate District	State of N	lew Mexico		
Office	Energy, Minerals a	nd Natural Resouces		
<u>DISTRICT I</u>			FORM C-103	
1625 N. French Dr., Hobbs, NM 88240			Revised March 25, 1999	
DISTRICT II	OIL CONSERVA	ATION DIVISION	WELL API NO.	
811 South First, Artesia, NM 88210	2040 Sou	th Pacheco	30-025-34805	
DISTRICT III	Santa Fe, NM 87505		5. Indicate Type of Lease	
1000 Rio Brazos Rd., Aztec, NM 87410			STATE FEE	
DISTRICT IV			6. State Oil & Gus Lease No.	
2040 South Pacheco, Santa Fe, NM 87505			22503	
SUNDR	Y NOTICES AND REPORTS OF	N WELLS		
(DO NOT USE THIS FORM FOR	PROPOSALS TO DRILL OR TO DEEPH	EN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name	
DIFFERENT RESERVOIR. USE	"APPLICATION FOR PERMIT" (FORM	C-101) FOR SUCH		
PROPOSALS.)			Northeast Drinkard Unit	
1. Type of Well:				
✓ OIL WELL	GAS WELL OTHER			
2. Name of Operator		·-	8. Well No.	
Apache Corporation			834	
3. Address of Operator			9. Pool name or Wildcat	
2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400		Eunice N., Blinebry-Tubb-Drinkard		
Unit Letter G	: 2462. Feet From The NO.	rth Line and 2495	Feet From The East Line	
			· · · · · · · · · · · · · · · · · · ·	
Section 23	Township 21S Range 210. Elevation (Show whether I	37E NMPM	Lea County	
	3389' GR			
11.		ate Box to Indicate Nature of Notice,	Report, or Other Data	
NOTICE OF	INTENTION TO:	SUB	SEQUENT REPORT OF:	
Perform Remedial Work	Plug and Abandon	Remedial Work	Altering Casing	
Temporarily Abandon	Change Plans	🗹 Commence Drill	ing Operations 🔲 Plug and Abandonment	
Pull or Alter Casing		Casing Test and	Cement Job	
Other		✓ Other	Surface & Production Casing	

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

.

- 2/12/00 Drilled 12-1/4" hole to 1216'. Ran 29 jts 8-5/8" 24# J-55 ST&C casing. Cemented w / 460 sx Class "C". Circulated 114 sx to pit.
- 2/26/00 Drilled 7-7/8" hole to 6779'. Ran 155 jts 5-1/2" 17# J-55 LT&C casing. Cemented w / 850 sx 35/65 POZ "C" & 475 sx 50/50 POZ "H". Cemented did not circulate. Top of float collar @ 6688' Top of float shoe @ 6777'

TYPE OR PRINT NAME Deb	no I / n doman		
	ra J. Anderson	TELEPHONE NO.	713-296-6338
(This space for State Use)			
APPROVED BY	TITLE	DATE	