state of New Mexico Submit 3 Copies To Appropriate District Form C-103 Office Energy, Minerals and Natural Resources Revised March 25, 1999 District I WELL API NO. 1625 N. French Dr., Hobbs, NM 87240 District II 30-025-34818 OIL CONSERVATION DIVISION 811 South First, Artesia, NM 87210 5. Indicate Type of Lease 2040 South Pacheco District III 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 STATE x FEE \square District IV 6. State Oil & Gas Lease No. 2040 South Pacheco, Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Outland State Unit Oil Well Gas Well Other 2. Name of Operator 8. Well No. Santa Fe Snyder Corporation **1Y** 3. Address of Operator 9. Pool name or Wildcat 550 W. Texas, Suite 1330, Midland, TX 79701 Wilson Morrow Gas 4. Well Location Unit Letter 638 feet from the 739 line and_ feet from the West line Section 12 Township 21S Range 34E **NMPM** County 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3676 GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING** TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND **ABANDONMENT PULL OR ALTER CASING** MULTIPLE **CASING TEST AND** COMPLETION **CEMENT JOB** OTHER: OTHER: Set Intermediate Csg X 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 1-13-00 Drill 12 1/4" hole to a depth of 5750'. GIR W/ 9 5/8" 40# casing set @ 5750'. Shoe set @ 5750' collar set @ 5670'. Circ csg. Cement 1st stage w/ 265 sx 50/50 Poz + 10% gel + 5% salt. Tail w/ 300 sx Class 'C' + 1% CaCl. Bump plug @ 8 am. Press up pkr, drop dart, open DV tool, circ. Cement 2nd stae w/ 2000 sx 50/50 Poz + 10% gel + 8% salt. Tail w/ 200 sx Class 'C' + 1% CaCl. Plug down @ 2 pm. WOC. Will continue drilling 8 3/4" hole. I hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE Regulatory Specialist _DATE_ Type or print name Bill Keathbly Telephone No. 915-686-6612 4):NG NORN PERSON LINE (This space for State use) APPROVED BY TITLE DATE

Conditions of approval, if any:

