Submit 3 Copies to Approriate District		ew Mexico				
Office	Energy, Minerals and Natural Resouces					
<u>DISTRICT I</u>			FORM C-103			
1625 N. French Dr., Hobbs, NM 88240			Revised March 25, 1999			
DISTRICT II	OIL CONSERVATION DIVISION		WELL API NO.			
811 South First, Artesia, NM 88210	2040 South Pacheco		30-025-34887			
DISTRICT III	Santa Fe, NM 87505		5. Indicate Type of Lease			
1000 Rio Brazos Rd., Aztec, NM 87410			STATE FEE			
DISTRICT IV			6. State Oil & Gas Lease No.			
2040 South Pacheco, Santa Fe, NM 87505						
SUNDRY NOTICES AND REPORTS ON WELLS						
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			7. Lease Name or Unit Agreement Name			
PROPOSALS.)			Northeast Drinkard Unit			
1. Type of Well:						
🗹 OIL WELL	GAS WELL OTHER					
2. Name of Operator			8. Well No.			
Apache Corporation			624			
3. Address of Operator			9. Pool name or Wildcat			
2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400			Eunice N., Blinebry-Tubb-Drinkard			
Unit Letter <u>C</u> :	1250 Feet From The NO	rth Line and 1368	Feet From The West Line			
Section 15 T	Township 21S Range	37E NN	IPM Lea County			
	10. Elevation (Show whether 1	DF, RKB, RT, GR, etc.)				
	3444' GR					
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data						
NOTICE OF I	UBSEQUENT REPORT OF:					
Perform Remedial Work		Remedial Wo	ork Altering Casing			
Temporarily Abandon	Change Plans	Commence Drilling Operations 🗌 Plug and Abandonment				
Pull or Alter Casing		Casing Test and Cement Job				
Other		V Other	Surface & Production Casing			

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/17/00 MIRU UTI Rig # 302. Spud well @ 3:30 pr	m
---	---

- 4/18/00 Drilled 12-1/4" hole to 1213'. Ran 29 jts 8-5/8" 24# K-55 ST&C casing. Cemented w/ 460 sx Class "C". Circulated 82 sx to pit
- 5/2/00 Drilled 7-7/8" hole to 6860'. Ran 165 jts 5-1/2" 17# J-55 LT&C casing. Cemented w/ 900 sx 35/65 POZ "C" & 500 sx 50/50 POZ "H". Circulated 100 sx to pit. Top of float collar @ 6776'. Top of float shoe @ 6858'. Rig released @ 6:00 am

	[
I hereby certify that the information above is true	and complete to the best of my knowledge and belief.			
signature	Chickbell TILE	Sr. Engineering Technician	DATE	5/3/00
TYPE OR PRINT NAME Debra J.	Inderson		TELEPHONE NO.	713-296-6338
(This space for State Use)				
- (
APPROVED BY	TITLE		DATE ,	
CONDITIONS OF APPROVAL, IF ANY:				. କଳ୍କର୍ଯ