Form C-103 State of New Mexico Submit 3 Copies To Appropriate District Energy, Minerals and Natural Resources Revised March 25, 1999 Office District I WELL API NO. 1625 N. French Dr., Hobbs, NM 87240 30-025-35055 OIL CONSERVATION DIVISION District II 5. Indicate Type of Lease 811 South First, Artesia, NM 87210 2040 South Pacheco District III STATE **x** FEE 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 District IV 6. State Oil & Gas Lease No. 2040 South Pacheco, Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) State 'R' 1. Type of Well: Oil Well Gas Well Other 8. Well No. 2. Name of Operator Santa Fe Smyder Corporation 9. Pool name or Wildcat 3. Address of Operator Wilson Morrow Gas 550 W. Texas, Suite 1330, Midland, TX 79701 4. Well Location 990' feet from the South \_\_ line and\_\_\_\_ line Unit Letter 13 / M : 3300′ \_feet from the \_ NMPM County Township 21 S Range 34 E Section 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3708' 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND  $\mathbf{x}$ **TEMPORARILY ABANDON** CHANGE PLANS ABANDONMENT CASING TEST AND PULL OR ALTER CASING MULTIPLE CEMENT JOB COMPLETION  $\mathbf{x}$ OTHER: Set 9 5/8" Casing OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 7/17/00 Drilled 12 3/4" hole to a depth of 5760'. GIH W/ 130 jts 9 5/8" 40# csg set @ 5760'. Shoe set @ 5760', collar set @ 5712' and stage tool @ 4237'. First stage cement 150 sx Class 'C' + interfill, tail 200 sx Class 'C' + 2% CaCl, WOC. second stage cement 1750 sx Class 'C' + interfill, tail cement 100 sx Class 'C' + 2% CaCL. Circulate 42 sx to pit. WOC. Continue dirlling 8 3/4" hole to total depth. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 30 Howelly TITLE Regulatory Specialist \_\_ DATE \_\_\_\_\_\_ **7/24/00**\_\_ Telephone No. 915-686-6612 Type or print name Bill Keathly (This space for State use) APPROVED BY\_ Destaign

Conditions of approval, if any: