

## DRILLING PROGRAM

Attachment to Form 3160-3  
Chevron U.S.A. Inc.  
Eunice Monument South Unit #688  
2580' FSL & 1300' FWL  
Section 8, T21S, R36E  
Lea County, New Mexico

1. Geological Name of Surface Formation:

Aeolian

2. Estimated Tops Of Important Geological Markers:

Rustler	1189'
T/Salt	1269'
B/Salt	2639'
Queen	3451'
Grayburg	3776'
TD	4150'

3. Protection of Zones:

The fresh water sands will be protected by setting 9 5/8" casing at 500' and circulating cement to surface. The oil and gas zones will be protected with 7" casing to total depth and circulating cement to surface.

4. Casing Program:

	<u>Hole Size</u>	<u>Interval</u>	<u>Csg OD</u>	<u>Weight, Grade, Type</u>
<b>WITNESS</b>	12-1/4"	0- <sup>1225'</sup> <del>500'</del>	9-5/8"	36#, K-55, ST&C
	8-3/4"	0-4150'	7"	20#, K-55, LT&C

Cement Program:

<b>WITNESS</b>	9 5/8" Surface Casing:	Cemented to surface using Class "C"
	(12-1/4" hole)	+ 4% Gel + 3% salt, followed by Class "C" + 2% CaCl <sub>2</sub> .

RECEIVED  
SEP 18 '00

SLM  
ROGERS, NM