Submit 3 Copies to Approriate District

State of New Mexico

Office	Energy, Minerals and	d Natural Resouces				
<u>DISTRICT I</u>				FORM C-103		
1625 N. French Dr., Hobbs. NM 88240				Revised March 25, 1999		
DISTRICT II	OIL CONSERVAT	TION DIVISION	WELL API NO.	, , , , , ,		
811 South First, Artesia, NM 88210	1220 South St.		30-025-3	5271		
DISTRICT HI	Santa Fe, NM 87505		5. Indicate Type of Leas			
1000 Rio Brazos Rd., Aztec, NM 87410		2.2 2.000		STATE FEE		
DISTRICTIV			6. State Oil & Gas Lease			
1220 South St. Francis Dr., Santa Fe, NM 87505						
SUNDRY	NOTICES AND REPORTS ON	WELLS				
(DO NOT USE THIS FORM FOR P	ROPOSALS TO DRILL OR TO DEEPEN APPLICATION FOR PERMIT" (FORM C-	7. Lease Name or Unit Agreement Name				
PROPOSALS.)	(Nor	theast Drinkard Unit		
1. Type of Well:			1 1101	moust Difficult Offic		
☑ OIL WELL	GAS WELL OTHER					
2. Name of Operator			8. Well No.			
Apache Corporation 3. Address of Operator			625			
			9. Pool name or Wildcat			
2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400 4. Well Location			Eunice N., Blinebry-Tubb-Drinkard			
Unit Letter E:	2580 Feet From The North	1 Line and 1300	Feet From The	West Line		
Section 15	Township 21S Range	37E NMPM	ı Lea	County		
10. Elevation (Show whether DF, RKB, RT, GR, etc.)						
	3442' GR					
11.	Check Appropriate	Box to Indicate Nature of Notice,	Report, or Other Da	ıta		
NOTICE OF INTENTION TO:			JBSEQUENT REPORT OF:			
Perform Remedial Work	Plug and Abandon	Remedial Work		Altering Casing		
☐ Temporarily Abandon	Change Plans	☑ Commence Dril	ling Operations	Plug and Abandonment		
Pull or Alter Casing		Casing Test and	Casing Test and Cement Job			
Other	her		Surface & Production Casing			
	leted operations. (Clearly state all perk). SEE RULE 1103. For Multiple					

or recompletion.

6/5/2001 MIRU Big Dog Rig # 9. Spud well @ 5:00 am

6/7/2001 Drilled 12-1/4" hole to 1219'. Ran 27 jts 8-5/8" 24# J-55 ST&C casing. Cemented w/ 460 sx

Class "C". Circulated 81 sx to pit

6/22/2001 Drilled 7-7/8" hole to 6840'. Ran 155 jts 5-1/2" 17# J-55 LT&C casing. Cement w/ 1000 sx

35/65 POZ "C" & 450 sx 50/50 POZ "H". Circulated 117 sx to pit. Top of float collar @ 6570'.

Top of float shoe @ 6838'. Released rig @ 8:00 am

I hereby certify that the information above is true and complete to the best of my kno	wledge and belief.					
SIGNATURE WOOD WILLIAM		TITLE _	Sr. Engineering Techni	cian	DATE	6/25/2001
TYPE OR PRINT NAME Debra J. Anderson				TELEPHO	NE NO.	713-296-6338
(This space for State Use)		. 				
APPROVED BY	TTILE	Orig	. Signed to	DATE		200 1
CONDITIONS OF APPROVAL, IF ANY:		7-2		_		
			•			•

