

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-35407
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. n/a
7. Lease Name or Unit Agreement Name: Wilson Deep Unit
8. Well No. 2
9. Pool name or Wildcat Wilson Morrow (Gas)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
Maynard Oil Company

3. Address of Operator
8080 N. Central Expwy. Suite 660, Dallas, TX. 75206

4. Well Location
Unit Letter D : 660 feet from the North line and 660 feet from the West line
Section 13 Township 21-S Range 34-E NMPM County Lea

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3664' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.
Plug & abandon the well due to severe deviation of the surface casing. Pumped 3 cement plugs as follows: Plug #1: Bottom hole plug- 5 sx. Class C cement from 1957' to 1839' (118'). Plug #2: Casing shoe plug- 50 sx. Class C cement 1450' to 1340' (110'). Plug #3: Surface plug- 10 sx. Class C cement from 45' to surface.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Gabe Utz TITLE Regulatory Engineer DATE 5/9/01

Type or print name Gabe Utz

Telephone No. 214-891-8454

(This space for State use)

APPROVED BY [Signature] TITLE [Signature] DATE [Signature]

Conditions of approval, if any: