

Submit 3 Copies to Appropriate District

Office

DISTRICT I

1625 N. French Dr., Hobbs, NM 88240

DISTRICT II

811 South First, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV

1220 South St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Drive
Santa Fe, NM 87505

FORM C-103
Revised March 25, 1999

WELL APIN NO. 30-025-35707
5. Indicate Type of Lease <input checked="" type="checkbox"/> STATE <input type="checkbox"/> FEE
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name State C Tract 12
8. Well No. 9
9. Pool name or Wildcat Penrose Skelly, Grayburg

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator

Apache Corporation

3. Address of Operator

2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400

4. Well Location

Unit Letter C : 600 Feet From The North Line and 1850 Feet From The West Line
Section 16 Township 21S Range 37E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3497' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

- ☐ Perform Remedial Work ☐ Plug and Abandon
☐ Temporarily Abandon ☐ Change Plans
☐ Pull or Alter Casing
☐ Other

- ☐ Remedial Work ☐ Altering Casing
☒ Commence Drilling Operations ☐ Plug and Abandonment
☐ Casing Test and Cement Job
☒ Other Surface & Production Casing

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

9/25/2001 MIRU Patterson Rig # 63. Spud well @ 5:15 pm

9/26/2001 Drilled 12-1/4" hole to 1218'. Ran 27 jts 8-5/8" 24# J-55 ST&C casing. Cemented w/ 325 sx 35:65 POZ "C" & 150 sx Class "C". Circulated 68 sx to pit

10/2/2001 Drilled 7-7/8" hole to 4200'. Ran 97 jts 5-1/2" 17# J-55 LT&C casing. Cemented w/ 450 sx 35:65 POZ "C" & 450 sx Class "C". Circulated 132 sx to pit. Top of float collar @ 4121'. Top of float shoe @ 4198'. Released rig @ 8:00 am

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Debra J. Anderson
Debra J. Anderson

TITLE

Sr. Engineering Technician

DATE

10/3/2001

TYPE OR PRINT NAME

TELEPHONE NO.

713-296-6338

(This space for State Use)

APPROVED BY

TITLE

ORIGINAL SIGNED BY
PAUL F. KAUTZ
PETROLEUM ENGINEER

DATE

10/3/2001

CONDITIONS OF APPROVAL, IF ANY: