

10-5/8	96#	8	L'weld 121'	7000' 0.0.0.				
15-1/2	70#	8	" 621'	" "	Full	-	Left Shoe in Hole	
12-1/2	50#	8	" 975'	JUN 23 '24	3 PM '26			
10	45#	8	" 1684'	" "				
8-5/8	36#	10	S'less 3590'	" "				

MUDDING AND CEMENTING RECORD

SIZE	WHERE SET	No. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	1684'	70 Sacks	Halliburton		
8-5/8"	3590'	70 "	"		

PLUGS AND ADAPTERS

Heaving plug—Material none Length _____ Depth Set _____
 Adapters—Material _____ Size _____

SHOOTING RECORD

SIZE	SHELL USED	EXPLOSIVE USED	QUANTITY	DATE	DEPTH SHOT	DEPTH CLEANED OUT
	Well not shot					

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
 Cable tools were used from Surface feet to 3771 TD feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing January 11, 1930 at 10 PM
 The production for the first 24 hours was 2028 barrels of fluid of which 100 % was oil; no %
 emulsion; no % water; and no % sediment. Gravity, Be. 31.4
 If gas well, cu. ft. per 24 hours no gas Gallons gasoline per 1,000 cu. ft. of gas _____
 Rock pressure, lbs. per sq. in. none

EMPLOYEES

Fred Lackey, Driller Carl Whan, Driller
D. E. L. Byers, Driller _____, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this _____
 day of 11 25, 1930

Name _____

Position District Superintendent

Representing The Texas Company

Notary Public
 My commission expires _____

Company or Operator