GEOLOGICAL SURVEY

Form 9-881 a (Feb. 1951)

		ND REPORTS ON WELLS	·		
NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF.			
		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.			
NOTICE OF INTENTION TO TEST WATER SH NOTICE OF INTENTION TO RE-DRILL OR RI		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.			
NOTICE OF INTENTION TO SHOOT OR ACID					
NOTICE OF INTENTION TO PULL OR ALTER					
NOTICE OF INTENTION TO ABANDON WELL					
			·		
(INDICATE ABO	OVE BY CHECK MARK NA	TURE OF REPORT, NOTICE, OR OTHER DATA)			
		yay 15			
		•	10		
		4010 MA	•		
Vell No is located	2510 6 6 1	(N_{ij}, \dots, ij)	35		
is located	tt. from	$\{\mathbf{x}^{\mathbf{y}}\}$ line andft. from $\{\mathbf{w}^{\mathbf{y}}\}$ line of second			
MV t of Sec. 35	23 5 1	SATE CTT			
(1/2 Sec. and Sec. No.)	(Twp.) (Rai	nge) (Meridian) TOWN MORESCO			
(Field)	///				
(2.004)	(County or Su	(**************************************			
ne elevation of the derrick floor	above see level	3575.7			
	DETAILS	OF WORK			
tate names of and expected depths to object i:	ive sands: show sives w	rainble and locate of	obs, ceme		
	ive sands; show sizes, w ng points, and all other	reights, and lengths of proposed casings; indicate mudding joint important proposed work)	obs, ceme		
Orill 12-1/4" surface	tive sands; show sizes, wing points, and all other in hole	reights, and lengths of proposed casings; indicate mudding jo important proposed work)	obs, ceme		
Orill 12-1/4" surface Set 300' of 8-5/8" ca	tive sands; show sizes, wing points, and all other a hole asing and cirr	reights, and lengths of proposed casings; indicate mudding joint proposed work)	obs, ceme		
0rill 12-1/4" surface Set 300' of 8-5/8" ca Drill 7-7/8" hole to	ive sands; show sizes, wing points, and all other hole asing and cire approximately	reights, and lengths of proposed casings; indicate mudding joint in the proposed work) 101ate cament w/150 Sam 5200	obs, ceme		
0rill 12-1/4" surface Set 300' of 8-5/8" ca Drill 7-7/8" hole to	ive sands; show sizes, wing points, and all other hole asing and cire approximately	reights, and lengths of proposed casings; indicate mudding joint proposed work)	obs, ceme		
0rill 12-1/4" surface Set 300' of 8-5/8" ca Drill 7-7/8" hole to	ive sands; show sizes, wing points, and all other hole asing and cire approximately	reights, and lengths of proposed casings; indicate mudding joint in the proposed work) 101ate cament w/150 Sam 5200	obs, ceme		
0rill 12-1/4" surface Set 300' of 8-5/8" ca Drill 7-7/8" hole to	ive sands; show sizes, wing points, and all other hole asing and cire approximately	reights, and lengths of proposed casings; indicate mudding joint in the proposed work) 101ate cament w/150 Sam 5200	obs, ceme		
0rill 12-1/4" surface Set 300' of 8-5/8" ca Drill 7-7/8" hole to	ive sands; show sizes, wing points, and all other hole ssing and cire approximately	reights, and lengths of proposed casings; indicate mudding joint in the proposed work) 101ate cament w/150 Sam 5200	obs, ceme		
0rill 12-1/4" surface Set 300' of 8-5/8" ca Drill 7-7/8" hole to	ive sands; show sizes, wing points, and all other hole ssing and cire approximately	reights, and lengths of proposed casings; indicate mudding joint in the proposed work) 101ate cament w/150 Sam 5200	obs, ceme		
0rill 12-1/4" surface Set 300' of 8-5/8" ca Drill 7-7/8" hole to	ive sands; show sizes, wing points, and all other hole ssing and cire approximately	reights, and lengths of proposed casings; indicate mudding joint in the proposed work) 101ate cament w/150 Sam 5200	obs, ceme		
0rill 12-1/4" surface Set 300' of 8-5/8" ca Drill 7-7/8" hole to	ive sands; show sizes, wing points, and all other hole ssing and cire approximately	reights, and lengths of proposed casings; indicate mudding joint in the proposed work) 101ate cament w/150 Sam 5200	obs, ceme		
0rill 12-1/4" surface Set 300' of 8-5/8" ca Drill 7-7/8" hole to	ive sands; show sizes, wing points, and all other hole ssing and cire approximately	reights, and lengths of proposed casings; indicate mudding joint in the proposed work) 101ate cament w/150 Sam 5200	obs, ceme		
0rill 12-1/4" surface Set 300' of 8-5/8" ca Drill 7-7/8" hole to	ive sands; show sizes, wing points, and all other hole ssing and cire approximately	reights, and lengths of proposed casings; indicate mudding joint in the proposed work) 101ate cament w/150 Sam 5200	obs, ceme		
Orill 12-1/4" surface Set 300' of 8-5/8" ca Drill 7-7/8" hole to Set 4-1/2" casing at	ive sands; show sizes, wing points, and all other choices as ing and ciru approximately approximately	reights, and lengths of proposed casings; indicate mudding is important proposed work) Rulate cament w/150 sam y 5200° y 5200°; cament w/200 sam cayant			
Orill 12-1/4" surface Set 300° of 8-5/8" can Drill 7-7/8" hole to Set 4-1/2" casing at	ive sands; show sizes, wing points, and all other choices as ing and ciru approximately approximately	reights, and lengths of proposed casings; indicate mudding joint in the proposed work) 101ate cament w/150 Sam 5200			
Orill 12-1/4" surface Set 300° of 8-5/8" can Drill 7-7/8" hole to Set 4-1/2" casing at understand that this plan of work must room A. G. McCaryer	ive sands; show sizes, wing points, and all other choices as ing and ciru approximately approximately	reights, and lengths of proposed casings; indicate mudding is important proposed work) Rulate cament w/150 sam y 5200° y 5200°; cament w/200 sam cayant			
Orill 12-1/4" surface Set 300° of 8-5/8" ca Drill 7-7/8" hole to Set 4-1/2" casing at A. G. McCarver mpany	ive sands; show sizes, wing points, and all other concessions and circ approximately approximately approximately	reights, and lengths of proposed casings; indicate mudding is important proposed work) Rulate cament w/150 sam y 5200° y 5200°; cament w/200 sam cayant			
Orill 12-1/4" surface Set 300° of 8-5/8" ca Drill 7-7/8" hole to Set 4-1/2" casing at A. G. McCarver mpany	ive sands; show sizes, wing points, and all other concessions and circ approximately approximately approximately	reights, and lengths of proposed casings; indicate mudding is important proposed work) Dulate coment w/150 sam J 5200 J 5200 J 5200 Same t w/200 sam commit w/200 sam J 5200 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640	enced.		
Orill 12-1/4" surface Set 300° of 8-5/8" ca Drill 7-7/8" hole to Set 4-1/2" casing at A. G. McCarver mpany 1004 V & J Tower dress	ive sands; show sizes, wing points, and all other concessions and circ approximately approximately approximately	reights, and lengths of proposed casings; indicate mudding is important proposed work) Dulate coment w/150 sam J 5200 J 5200 J 5200 Same t w/200 sam commit w/200 sam J 5200 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640	enced.		
Orill 12-1/4" surface Set 300 of 8-5/8" ca Drill 7-7/8" hole to Set 4-1/2" casing at I understand that this plan of work must re A. G. McCarver mpany	ive sands; show sizes, wing points, and all other concessions and circ approximately approximately approximately	reights, and lengths of proposed casings; indicate mudding is important proposed work) Dulate coment w/150 sam J 5200 J 5200 J 5200 Same t w/200 sam commit w/200 sam J 5200 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640	enced.		
Orill 12-1/4" surface Set 300 of 8-5/8" ca Drill 7-7/8" hole to Set 4-1/2" casing at I understand that this plan of work must re A. G. McCarver mpany	ive sands; show sizes, wing points, and all other concessions and circ approximately approximately approximately	reights, and lengths of proposed casings; indicate mudding is important proposed work) Rulate cament w/150 sam y 5200° y 5200°; cament w/200 sam cayant	enced.		
Orill 12-1/4" surface Set 300' of 8-5/8" ca Drill 7-7/8" hole to Set 4-1/2" casing at A. G. McCarver ompany 1004 V & J Tower ddress	ive sands; show sizes, wing points, and all other concessions and circ approximately approximately approximately	reights, and lengths of proposed casings; indicate mudding is important proposed work) Dulate coment w/150 sam J 5200 J 5200 J 5200 Same t w/200 sam commit w/200 sam J 5200 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640 J 640	enced,		

N MIPER 'F COPIE	SRECEIVES	
015	TRIBUTION	
ANTA FF		
FILE		
U.S.G.5		
LAND OFFICE		
TRANSPORTER	OIL	
	GA5	
PROBATION OFFI	E	

..EW MEXICO OIL CONSERVATION MMISSION

FORM C-128 Revised 5/1/57

U.S.G.S LAND OFFICE		WELL LOCAT	ION AND ACREA	GE DEDICA	TION PLAT
TRANSPORTER GAS		SEE INSTRUCTIONS	FOR COMPLETING TH	HS FORM ON THE	REXERSE SIDE
PROBATION OFFICE				# F F E	
OPERATOR			65.6710:::		
Operator			Lease	LNG ES YA	1 - 36 Well No.
	lling Co.		Federal Pay	ne	1
Unit Letter	Section 2.5	Township	Range	County	
Actual Footage Lo	35	T 23S	R32E	Lea	<u>a</u>
2310	feet from the	North line and	d 231 0 fe	eet from the	West line
Ground Level Elev	Producing F		Pool		Dedicated Acreage:
3678.7	Delaw	are Sand	Legg		40 Acres
who has the rig another. (65- 2. If the answer to wise? YES	tht to drill into and 3-29 (e) NMSA 19 o question one is ' NO I	d to produce from any poo 35 Comp.)	ol and to appropriate the of all the owners been of Consolidation and their respective in	consolidated by co	("Owner" means the person for himself or for himself and mmunitization agreement or other-
A. G. McCarver XXX			Land Descri	=	3.7° 10
XXXXXXXX	WYYYYYYYY	(MA OI S	ec. 35, 23 S	36 8
AAAAAA					
		SECTION B			CERTIFICATION
	 	,		in ple bel	sition Owner
				Cor	npany G. McCARVER
					5 - 18 -61
				sho plot surv sup and	ereby certify that the well location wn on the plat in SECTION B was sted from field notes of actual weys made by me or under my ervision, and that the same is true correct to the best of my knowledge belief.
	90 1320 1650 19	80 2310 2640 200	00 1500 1000	Reg	e Surveyed 2-17-61 istered Professional Engineer /or Land Surveyor // Common Surveyor ificate No.

INSTRUCTIONS FOR COMPLETION OF FORM C-128

- 1. Operator shall furnish and certify to the information called for in Section A.
- 2. Operator shall outline the dedicated acreage for both oil and gas wells on the plat in Section B.
- 3. A registered professional engineer or land surveyor registered in the State of New Mexic or approved by the Commission shall show on the plat the location of the well and certify this information in the space provided.
- 4. All distances shown on the plat must be from the outer boundaries of the Section.
- 5. If additional space is needed for listing owners and their respective interests as required in question 3 of Section A, please use space below.