

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

A blank 10x10 grid with a small 'x' mark in the bottom-left cell.

Date 12-14-61 Title District Superintendent
The summary on this page is for the condition of the well at above date.
Commenced drilling 11-30-61, 1961 Finished drilling 12-11-61, 1961

(Don't put any 0's)

No. 1, from <u>NONE</u> to _____	No. 4, from _____ to _____
No. 2, from _____ to _____	No. 5, from _____ to _____
No. 3, from _____ to _____	No. 6, from _____ to _____

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

[illegible]

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
7-5/8"	371	200	Pump & Plug		

Heaving plug—Material _____ Length _____ Depth set _____
Adapters—Material _____ Size _____

[illegible]

Rotary tools were used from 0 feet to 5324 feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

-----, 19-----	Put to producing ----- Dry Hole -----, 19-----
The production for the first 24 hours was -----	barrels of fluid of which ----- % was oil; ----- %
emulsion; ----- % water; and ----- % sediment.	Gravity, °Bé. -----
If gas well, cu. ft. per 24 hours -----	Gallons gasoline per 1,000 cu. ft. of gas -----
Rock pressure, lbs. per sq. in. -----	

G. P. Stewart	, Driller
D. A. May	, Driller
L. W. White	, Driller
	, Driller

FROM—	TO—	TOTAL FEET	FORMATION
0	1370		Red Beds
1370	1620		Salt
1620	2160		Salt & Anhydrite
2160	2505		Salt
2505	3667		Anhydrite & Salt
3667	4138		Anhydrite
4138	4374		Salt
4374	4482		Anhydrite
4482	4812		Salt
4812	4983		Anhydrite
4983	5124		Anhydrite & Lime
5124	5324		Sand & Shale

TD 5324', KB 12', Elev 3710' KB, Surface casing 7 5/8" set at 371' W/200 Sx. This well was dry and plugged and abandoned upon completion 12-11-61. Ran G/R Sonic and Laterolog. No oil, water or gas encountered. Set plugs at 5124-5324' W/75 Sx, 1350-1450' W/75 Sx, 340-400' W/15 Sx and 5 Sx at surface. Intervals between plugs filled with 10.3 lb. mud. Erected 4" Marker extending 4' above surface with well name and location inscribed thereon. Approval of Mr. Standley, District Engineer, USGS obtained prior to commencement of plugging operations. Location restored to original condition. Tops: Rustler 900', Salt 1230', Base Salt 4814', Lamar Lime 5072', Dela Sd 5132'. Drlg started 11-30-61, Comp 12-11-61. Plugging started 12-11-61, Comp 12-11-61.

FORMATION RECORD—Continued[illegible]

HISTORY OF OIL OR GAS WELL

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

[illegible]