

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

N. M. OIL CONVEY. BOARD
P. O. BOX 1093
ROSWELL, NEW MEXICO 88240

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR

SHELL OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. BOX 991, HOUSTON, TX 77001

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FWL AND 660' FSL
AT TOP PROD. INTERVAL: SAME
AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☒ *PLUGGED BACK TO ATOKA
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-09-83: Set CIBP @ 13,100' and capped w/35' of cmt.
2-10-83: Installed production equipment w/Baker Model "DAB" pkr @ 11,725'.
2-15-83: Perf'd Atoka zone 12,093' to 12,465' (56 holes).
2-17-83: Acidized Atoka w/7,000 gals 15% Morrow flow BC acid containing 750 SCF N₂/bbl.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED A. J. FORE TITLE SUPV. REG. & PERM. DATE

ROSWELL, NEW MEXICO

MARCH 10, 1983

ACCEPTED FOR RECORD (is space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS

DATE

CONDITIONS OF APPROVAL SEP 07 1983

ROSWELL, NEW MEXICO

*See Instructions on Reverse Side