

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
SHELL OIL COMPANY

3. ADDRESS OF OPERATOR
P. O. BOX 991, HOUSTON, TX 77001

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL AND 660' FSL
AT TOP PROD. INTERVAL: SAME
AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☒ *
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐

* PLUG BACK TO ATOKA

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED

JAN 12 1983

OIL & GAS
MINERALS MGMT. SERVICE
ROSWEIL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

WE PROPOSE TO ABANDON THE MORROW ZONE AND RECOMPLETE TO THE ATOKA AS FOLLOWS:

1. Set CIBP @ 13,200' and cap w/35' of cmt (6 sx (Class "H" + .8% Halad-9).
2. Install production equipment (tbg open ended) w/pkr @ 11,725'.
3. Perforate (Atoka) 12,093' to 12,465' (56') thru tbg.
4. Acidize Atoka w/7,000 gals 15% Morrow flow BC acid containing 750 SCF N₂/bbl.
5. Flow test well.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. J. FORE TITLE SUPV. REG. & PERM. DATE JANUARY 10, 1983

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED

JAN 12 1983

JAMES A. GILLHAM
DISTRICT SUPERVISOR

RECEIVED

JAN 14 1983

**O.C.D.
HOBBS OFFICE**