

COPIES RECEIVED		
TRIBUTION		
FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Galport Oil Corporation	8. Farm or Lease Name A. ...
3. Address of Operator 2011 ...	9. Well No. 1
4. Location of Well UNIT LETTER "C" 1,700' FEET FROM THE East LINE AND 600' FEET FROM THE South LINE, SECTION 20 TOWNSHIP 22S RANGE 30S NMPM.	10. Field and Pool, or Wildcat South ...
15. Elevation (Show whether DF, RT, GR, etc.) Unknown	12. County ...

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Logs: 111. 3450', 5 5/8" Csg set at 311' +/- 200 sacks cmt., -5 1/2" Csg set at 2920' +/- 400 sacks cmt. - open hole from 2920' to 3450'.

Plugging Procedure

1. Set cast iron bridge plug at 2900' +/- 50 cmt., or spot 100' Plug in out of 5 1/2" Csg. at 2920'.
 2. Set 100' Plug at 5 1/2" out off stub.
 3. Set " " at 5 5/8" stub in & out.
 4. " 10 sacks cmt. Plug at surface, install dry hole marker.
- Old fluid be circulated w/ all plug set w/ saltwater killed mud.
Commission will be notified before spotting plugs.

7 1/2" 5 1/2" Csg. is pulled FROM BELOW THE TOP OF THE SPOT 100' PLUG IS REQUIRED AT THE TOP OF THE CSEG.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED **Shene Mulford** TITLE **Agent** DATE **3/19/76**

APPROVED BY TITLE DATE
CONDITIONS OF APPROVAL, IF ANY: