



## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED

LOCAT	AREA 640 A	ACRES CORRECTL	Y	UN	TIL FORI	# C-105 IS PE	PERLY PILLE	D OUT.			
West	ern Na	tural Company			ny	509	West T	exas Ave.	midlan	d, Texas	
***************************************	Owen Leas	18	7	Well No	1	inSW 4	Swig of Se	.c. 26	, T <b>2</b>	25	
r36 <b>E</b> .		N M F	. м.,	outh E	unice	Field,		L <b>e</b> ą		County.	
								line of Se		2-36	
								Lam		G <b>G</b>	
								Address Pan			
								Address Mid			
							-	ted June			
_							_	Address Lub			
						feet.					
The inform	mation giv	en is to b	e kept c	onfidential	l until	Not cor	ifidenti.	a <b>1</b>	19		
						SANDS OR Z					
1101 07 110				V		PANT WATE					
Include d	lata on rat	te of wate	r inflow	and eleva		hich water ro					
								feet			
•								feet			
•								feet			
No. 4, fro	m			t				feet		***************************************	
					C/	ASING RECO	RD				
SIZE	WEIGHT PER FOO	THR T PER	EADS INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLI FROM	ED PERF FROM	ORATED TO	PURPOSE	
13 3/	8 32	,	8	Navlo	r 30*			FROM		Conductor	
9 5/8			8	Nat'l	1491	Howco				Salt	
7"	24,	ř	8	Nat'l	3085	* Howeo			187 ga	Productio	
	_									_	
	<u> </u>			<u> </u>		<u> </u>			<u> </u>	<u> </u>	
				MITIT	DING A	ND CEMENT	ING RECORI	<b>D</b>			
							1				
SIZE OF HOLE	CASING	WHERE S	ET (	NO. SACKS OF CEMENT	MI	THODS USED	MUD 6	RAVITY	AMOUNT OF	MUD USED	
174	13 3/	30		20	На	nd mix					
- 1	9 5/8	150	• 1	750	F	lliburt	. 1				
8 3/	4	309		300	ns	lliburt					
						8 AND ADA					
								Depth Set.			
Adapters-	Material								,.		
			R	ECORD OF	SHOOT	ING OR CHE	MICAL TREA	ATMENT		·	
SIZE	SHELI	SHELL USED		LOSIVE OR ICAL USED	ı Qı	JANTITY	DATE	DEPTH SHOT OR TREATED	T DEPTH CLEANED OUT		
<u> </u>			156	uold	20	OO cale	June 23	3097-PD	-PD		
			**/P	- HV-44							
	)				<u> </u>		)				
Results of	shooting	or chemics	al treatn	nentpr	od uot	ion inc	reased f	rom 4,830	OF to	······································	
11,	.0004(	GFper	-day	•							
				RECORT A	יואת קס	L-STEM AN	D SPECIAL '	TESTS			
If drill-ata	em or othe	er special f						n separate sheet	and attach	hereto.	
			-		-	TOOLS USE					
Rotary to	ols were u	sed from	•	fe	et to	3580	feet, and from		feet to	feet	
Cable to	ols were u	sed from		fe	et to		eet, and from	***************************************	feet to	feet	
						PRODUCTIO	N				
				a			s of fluid of a	which	% was oil:	;	
								w Hieli			
If gas we	ell, cu. ft.	per 24 hou	ırs <b>11</b>	.000	900	Gallor	ıs gasoline per	1,000 cu. ft. of	gas?.		
Rock pres	ssure, lbs.	per sq. in.		230	~ <b>~ *</b>						
						EMPLOYEES	3				
<u>F</u>	is its	allen			<del>-</del>	Driller	T. S. l	ewie		, Driller	
••••••	Henry	Luco	ok			Driller		·		, Driller	
		•••	. •				OTHER SID		na wall and al	l work done on	
						with 18 a con	upiete and cor	rect record of th	ro well aud 81	WOLK HOUS OF	
it so far a	as can be	determine-	u irom	available r	. ocurus.						
Subscribe	ed and swo	orn to befo	re me t	h <b>is</b>				Pexas			
day of		•••••		************	, 19.	Na	me toul	C. Way	let, Ja		
						Po	sition	colour e	nginter	<u>)</u>	
			j	Notary Pul	blic	Re	presenting	western N	operator Gos	<del>-</del> 0-₃	

Address 509 W. Texas, midland, Tex.

My Commission expires.....

## FORMATION RECORD

			DRMATION RECORD				
FROM	то	THICKNESS IN FEET	FORMATION				
0 30 1490 1 <b>5</b> 80 2900 2980 3090 3195	30 1490 1580 2900 2980 3090 3195 3580	30 1460 90 1420 80 110 105 385	Caliche Red Sand and Shale Anhydrite and dolomite Salt and Anhydrite Stringers Anhydrite Brown dolomite and anhydrite Sand and anhydrite Dolomite and sand				
	•	·					
·							