

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

|                        |  |
|------------------------|--|
| NO. OF COPIES RECEIVED |  |
| DISTRIBUTION           |  |
| SANTA FE               |  |
| FILE                   |  |
| U.S.G.S.               |  |
| LAND OFFICE            |  |
| OPERATOR               |  |

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL  GAS WELL  OTHER- P&A

7. Unit Agreement Name

Name of Operator ARCO Oil & Gas Company  
Division of Atlantic Richfield Company

8. Farm or Lease Name  
Shipley <sup>ck</sup> WN

Address of Operator  
P. O. Box 1710, Hobbs, New Mexico 88240

9. Well No.  
1

Location of Well  
UNIT LETTER C 990 FEET FROM THE North LINE AND 1650 FEET FROM  
THE West LINE, SECTION 27 TOWNSHIP 22S RANGE 36E NMPM.

10. Field and Pool, or Wildcat  
Jalmat Yates 7R

15. Elevation (Show whether DF, RT, GR, etc.)  
3509' GR

12. County  
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK   
TEMPORARILY ABANDON   
PULL OR ALTER CASING   
OTHER

PLUG AND ABANDON   
CHANGE PLANS

REMEDIAL WORK   
COMMENCE DRILLING OPNS.   
CASING TEST AND CEMENT JOB   
OTHER

ALTERING CASING   
PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

P&A procedure approved verbally by Mr. L. Clements w/OCD 3/24/81.

1. Rig up on 4/21/81. POH w/rods & pump, install BOP. POH w/tbg. Ran bit & scraper to 3141' top of liner.
  2. Set pkr @ 3066' & established injection rate of 4 BPM @ 1200#.
  3. RIH w/cmt retr, set retr @ 3066'. Pumped 50 sx Cl C cmt w/2% CaCl<sub>2</sub> thru retr w/1500#. Spot 10 sx Cl C cmt w/2% CaCl<sub>2</sub> on top of retr.
  4. Spot Cl C cmt w/2% CaCl<sub>2</sub> 1500-1750'. Spot 10' sx cmt @ surf. Install regulation dry hole marker. Clean & Level location for abandonment.
- P&A eff: 4/23/81.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W.D. McWain J.W. Schmidt TITLE Dist. Drlg. Supt.

DATE 4/28/81

APPROVED BY Daniel Calanack TITLE OIL & GAS INSPECTOR

DATE NOV 28 1981

CONDITIONS OF APPROVAL, IF ANY: