

U. S. LAND OFFICE Las Cruces
SERIAL NUMBER LC 030133 (b)
LEASE OR PERMIT TO PROSPECT _____UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

LOCATE WELL CORRECTLY

Company Continental Oil Company Address Box 427, Hobbs, N.M.
Lessor or Tract Meyer B-28 Field South Eunice State New Mexico
Well No. 3 Sec. 28 T. 22S R. 36E Meridian NMPM County Lea
Location 660 ft. N of N Line and 660 ft. E of E Line of Sec. 28 Elevation 3517'
(Derrick floor relative to sea level)The information given herewith is a complete and correct record of the well and all work done thereon
so far as can be determined from all available records.Signed _____ Title District SuperintendentDate November 29, 1955

The summary on this page is for the condition of the well at above date.

Commenced drilling October 26, 1955 Finished drilling November 3, 1955

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 3680 to 3810 No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
<u>8 5/8</u>	<u>21 1/2</u>	<u>8R</u>	<u>J-55</u>	<u>1472'</u>	<u>Guide Shoe</u>				
<u>5 1/2</u>	<u>16 5/8</u>	<u>8R</u>	<u>J-55</u>	<u>1087'</u>	<u>Guide Shoe & Fleet Collar</u>				
<u>5 1/2</u>	<u>16 5/8</u>	<u>8R</u>	<u>J-55</u>	<u>1087'</u>					
<u>5 1/2</u>	<u>16 5/8</u>	<u>8R</u>	<u>J-55</u>	<u>789'</u>					
<u>5 1/2</u>	<u>17#</u>	<u>8R</u>	<u>N-80</u>	<u>551'</u>					
<u>5 1/2</u>	<u>17#</u>	<u>8R</u>	<u>J-55</u>	<u>95'</u>					
<u>5 1/2</u>	<u>23#</u>	<u>8R</u>	<u>N-80</u>	<u>111'</u>					

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
<u>8 5/8</u>	<u>1474</u>	<u>600</u>	<u>Pump & Plug</u>		
<u>5 1/2</u>	<u>3814</u>	<u>944</u>	<u>Pump & Plug</u>		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____
Adapters—Material _____ Size _____

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

TOOLS USED

Rotary tools were used from 0 feet to 3815 feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

DATES

_____, 19____ Put to producing November 11, 1955The production for the first 24 hours was 220 barrels of fluid of which 100 % was oil; _____ %
emulsion; _____ % water; and _____ % sediment. Gravity, °Bé. 32

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

J. B. Howell, Driller G. V. Grant, Driller
F. N. Down, Driller _____, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
<u>0</u>	<u>41</u>	<u>41</u>	<u>Sand & Shale</u>
<u>41</u>	<u>240</u>	<u>299</u>	<u>Sand, Shale & Shells</u>
<u>240</u>	<u>777</u>	<u>437</u>	<u>Redbed</u>
<u>777</u>	<u>875</u>	<u>98</u>	<u>Redbed & Shells</u>
<u>875</u>	<u>1095</u>	<u>220</u>	<u>Redbed & Shale</u>
<u>1095</u>	<u>1370</u>	<u>275</u>	<u>Redbed, Shale & Sand</u>
<u>1370</u>	<u>1388</u>	<u>18</u>	<u>Anhydrite & Shale</u>
<u>1388</u>	<u>1727</u>	<u>399</u>	<u>Anhydrite, Shale & Sand</u>
<u>1727</u>	<u>2236</u>	<u>509</u>	<u>Anhydrite, Shale & Salt</u>
<u>2236</u>	<u>2540</u>	<u>304</u>	<u>Anhydrite & Salt</u>
<u>2540</u>	<u>2648</u>	<u>108</u>	<u>Anhydrite, Salt & Gyp</u>
<u>2648</u>	<u>3013</u>	<u>365</u>	<u>Anhydrite & Salt</u>
<u>3013</u>	<u>3020</u>	<u>7</u>	<u>Anhydrite</u>
<u>3020</u>	<u>3086</u>	<u>66</u>	<u>Anhydrite & Lime</u>
<u>3086</u>	<u>3124</u>	<u>38</u>	<u>Anhydrite, Lime & Gyp</u>
<u>3124</u>	<u>3170</u>	<u>46</u>	<u>Anhydrite & Lime</u>
<u>3170</u>	<u>3205</u>	<u>35</u>	<u>Anhydrite, Lime & Gyp</u>
<u>3205</u>	<u>3368</u>	<u>163</u>	<u>Anhydrite & Lime</u>
<u>3368</u>	<u>3431</u>	<u>63</u>	<u>Lime</u>
<u>3431</u>	<u>3454</u>	<u>23</u>	<u>Lime & Shale</u>
<u>3454</u>	<u>3815</u>	<u>361</u>	<u>Lime</u>

[OVER]

