Torm \$331ppis COMMISSION	Budget Bureau No. 42-R1424
O BOX 1969 UN: STATES 10386 KIW DEPARTMENT OF THE INTERIOR	5. LE LC - 030/33 (B)
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME NMFU 8. FARM OR LEASE NAME South Eunice Unit
1. oil gas well other Water Inj	9. WELL NO. 39
2. NAME OF OPERATOR CONOCO INC.	10. FIELD OR WILDCAT NAME Eunice 7 Rivers Queen
3. ADDRESS OF OPERATOR P. O. Box 460, Hobbs, N.M. 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec. 28, T- 225, R-36E
below.) AT SURFACE: 1980' FNL + 1980' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF:	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine MIRU. Tag @ 3774. CO from	m 3774'- 3797'. Mil
out to 3740'-3745. DO from	n 3749'- 3795'. Set 9 BBLs 15 7. HCL-NE-F
Flush w/30 BBLs 9# brine	. Place Well on injection.
Inj. 10 BWPD@ 910 psi on	8-18-84.
Subsurface Safety Valve: Manu. and Type	Set @ Ft
18. I hereby certify that the foregoing is true and correct SIGNED TITLE Administrative Super ACCEPTED FOV RECORD This space for Federal or State	
ACCEPTED FOY RECORUThis space for Federal or State	office use)
ACCEPTED FOW RECORDING Space for Federal or State. APPROVED BY TITLE CONDITIONS OF APPROVAL ANY ANY OCT 2: 1984	DATE

Carlabati NEW MEXICO *See Instructions on Reverse Side