

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well

☒ Other *Injection*

2. Name of Operator

Conoco Inc.

3. Address and Telephone No.

10 Desta Drive, Ste 100 W, Midland, TX 79701 686-5494

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660 FSL & 660 FWL

Unit letter M, Sect. 28, T22S, R36E

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

South Eunice Unit No. 50

9. API Well No.

30-025-09083

10. Field and Pool, or Exploratory Area

Eunice 7 Rvrs Queen South

11. County or Parish, State

Lea, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing

☒ Other *Install liner*

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give percent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

11-9-90 MIRM. BIH w/4 3/4" bit + 5 1/2" csg scraper to 3812. BIH w/4" centralized perf gun w/CCL loaded. 2 jspt 0.40" EHD 180° phasing. Perf Seven Rvrs Queen from 3666-73, 3684-98, 3717-18, 3723-26, 3728-49, 3772-82, 3789-92, 3794-97, total 126 shots. Dump 19.5 SKS sand down csg. WO sand 1m tagged TDS at 3700. Let sand settle 1m tag. TDS and at 3671. Dump 2 SKS sand. BIH w/sinker bar tag. Top of sand at 3650. BIH w/4 3/4" bit + 2 3/8" WS. Circ out sand to 3666. POH. BIH w/4" bailer. Spot 1/2 SKS Cal Seal. Wait on Cal Seal. Tag top of Cal Seal at 3659.
11-14-90 BIH w/bushings 3 1/2" float shoe + collar w/2' aluminum cement. Sub 5' x 2 8/12" seal bore ext. Ran 23 jts 3 1/2" fiberglass csg. Ran 2 1/16" cementing string inside liner. Make up Buib magnum GT liner hanger per assembly. Circ through liner. BIH w/liner on 2 3/8" tag to 3659. Pmp 22 bbls Class "C" cmt. Set pcr release setting tool. Pmpd 337 SKS Class "C" cmt

14. I hereby certify that the foregoing is true and correct

Signed *Christine L. Neff*

Title *Admin. Assistant*

Date *6-22-91*

(This space for Federal or State office use)

Approved by
Conditions of approval, if any:

FOR RECORD ONLY

OCB

AUG 27 1991