

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

8910115860

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

South Eunice Unit No. 5

9. API Well No.

30-025-09083

10. Field and Pool, or Exploratory Area

Eunice 7 Rvs Queen So.

11. Country or Parish, State

Lea, nm

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well

☐ Gas Well

☒ Other

Injection

2. Name of Operator

Conoco Inc.

3. Address and Telephone No.

10 Dista Dr. Suite 108 W, Midland, TX

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit letter M, Sect. 28, T22S, R36E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Alarming Casing

☒ Other Install liner

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Squeeze to 1500# PU to TOL. Reverse out. Cmt. BBH to 3647 reverse out inside liner. BIH w/2 3/4" bit 2 1/16 + 2 3/8" WS. Tagged top of seal bore ext at 3653 Tst csg + liner to 500# - HELD. Drill out seal bore ext from 3653 to 54. Trip bit. DO to 3655. Con't drag out w/2 3/4" bit 2 1/16 + 2 3/8" WS. DO seal bore ext from 3655-56. Cmt from 3656-3659. Cal seal from 59-66. Co sand to TD 3812. Circ hole clean. BIH w/3.0 seal nipple, anchor seal assembly + 2 3/8" PC + bg. RU to circ. Circ 8 BBLs Conoco PU fluid. Latch + bg into plr at 2960 PSI + st backside to 500# for 15 min - HELD. RD.

14. I hereby certify that the foregoing is true and correct

Signed

Christine Neff

Title

Admin Assistant

Date

6-22-91

(This space for Federal or State office use)

Approved by

Title

Date

Continued on approval, if any: