

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
~~3002509089~~ 30-025-09084

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE 'APPLICATION FOR PERMIT'
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator

Conoco Inc.

3. Address of Operator

10 Desta Dr., Ste 100W, Midland, Tx 79705

4. Well Location

Unit Letter N : 330' Feet From The South Line and 1650' Feet From The West Line

Section 28 Township 22S Range 36E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3505' GL

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

It is proposed to plug & abandon the S. Eunice Unit No. 49 as follows:

1. POOH w/rods & pump. Tag for fill w/2-7/8" tubing & tally out of hole.
2. RIH w/5-1/2" cmt retainer on 2-7/8" tbq. Set retainer @ 3600'.
3. Squeeze perfs with 75 sx Class 'C' cmt. Displace cmt thru retainer. Sting out of retainer & place excess cmt on top.
4. RIH w/2-7/8" tbq & tag top of cmt. Load csg w/84 bbls of salt gel mud consisting of 10 ppg brine w/25 lbs of gel per bbl.
5. Spot 25 sx Class 'C' cement plug across top of salt section (1700'). Displace w/5 bbls of 10 ppg mud.
6. Perf @ 375' w/4 JSPF. Attempt to establish circ up the csg/csg annulus w/prod water.
7. Pump 100 sx Class 'C' cmt. Displace cmt to fill at least 100' of the 5-1/2" csg & circ cmt up the csg/csg annulus.
8. Cut off all csg strings at the base of cellar or 3' below final restored ground level.
9. Cover wellbore w/metal plate. Erect abandonment marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bill Keathly TITLE Sr. Regulatory Analyst DATE 09-17-92

TYPE OR PRINT NAME Bill Keathly (915) 686-5400 TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON

DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

SEP 21 '92
THE COMMISSION MUST BE NOTIFIED 24
HOURS PRIOR TO THE BEGINNING OF
PLUGGING OPERATIONS FOR THE C-103
TO BE PLUGGED.