

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

8910115860

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

SOUTH EUNICE UNIT #47

9. API Well No.

30-025-090874

10. Field and Pool, or Exploratory Area

EUNICE 7 RVRS QUEEN, SO

11. County or Parish, State

LEA, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well

☐ Gas Well

☒ Other

INJECTION

2. Name of Operator

Conoco Inc.

3. Address and Telephone No.

10 Desta Drive STE 100W, Midland, TX 79705 (915)686-5424

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2210' FSL & 330' FEL, SEC. 28, T-22S, R-36E, UNIT LTR 'I'

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other INSTALL LINER

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

7-9-91 MIRU. RELEASE PACKER POOH. TAG FILL AT 3473'.
RIH W/ BULL DOG BAILER - CO TO TD 3803' POOH
DISMANTLE WH, REPLACE WELLHEAD & 5' OF 8 5/8" CSG.
GIH W/ 4" 10.46# CASING LINER TO 3800' CEMENT BACK TO SURFACE.
DRILL & CIRC SOFT CMT TO 3759', CIRC HOLE CLEAN.
FINISH DRILL OUT WIPER PLUG @ 3759' & CMT TO 3800'-CIRC HOLE CLEAN.
TEST LINER FROM SURFACE OT 3088' @ 500 PSI FOR 30 MIN. - HELD.
GIH PERF 3608-09, 3619-20, 3630-31 W/ 1 JSPF AND
3657-64, 3673-80, 3698-3700, 3710-20 & 3725-34 W/ 4 JSPF - POOH.
RIH W/ PACKER & 2 3/8 WS - SET PACKER AT 3495'.
RU BJ TITON PUMPED 6780 GAL 15% HCL W/ 800# SALT FOR BLOCKS.
RIH W/ 4" IPC GIBBERSON PACKER SET AT 3554', CIRC PKR FLUID.
RDMO.
RETURN WELL TO INJECTION

14. I hereby certify that the foregoing is true and correct

Signed

Title

SR. REGULATORY SPEC.

Date

6-3-92

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any