

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	XX	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
 SANTA FE, NEW MEXICO

Eunice, New Mexico
 (Place)

July 15, 1960
 (Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the State A-32

Continental Oil Company
 (Company or Operator)

Well No. 5 in J
 (Unit)

NW 1/4 SE 1/4 of Sec. 32, T. 22-S, R. 36-E, NMPM., Jalmat Pool

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was completed 12-29-47 at a TD of 3625' in Lime. CSG PT 5 1/2" at 3524', elevation 3501' KB, DF 6'. Well was subsequently plugged back to 3600'. Opened perforations in the Seven Rivers formation from 3562-68', 3574-80', and 3584-87'. Well is presently TSD.

We propose to rig up, install BOP, run CI retainer on wireline and set at 3525', run 2 1/2" test tubing w/retainer stringer and latch into retainer, squeeze below retainer w/100 sx of reg. W/4% Gel., reverse out excess and pull 2 1/2" TBG, perforate Yates 3512-3522' W/4 jets/ft., run 2 1/2" TBG. W/TRT. PKR set Pkr., above 3493', acidize W/1000 gals of 15% LSTNE acid, swab load and test, pull TBG. W/PKR, perforate Yates 3493-3504' W/4 jets/ft., run TBG W/PKR, set PKR above 3493', sand frac W/8000 gals of lease crude, 8000# SD, 400# Adomite in 2 stages W/20 ball sealers between stages, swab load and test well.

Approved July 15 1960, 19____
 Except as follows:

Continental Oil Company
 (Company or Operator)

By [Signature]

Position District Superintendent
 Send Communications regarding well to:

Approved
 OIL CONSERVATION COMMISSION

By [Signature]

Name J. R. Parker

Title _____

Address Box 68, Eunice, New Mexico

O/2 NMCC 2-St Land Of WAM file