·	; =	-	
NO. OF COPIES ARCEIVED			Form C-103
DISTRIBUTION			Supersedes Old C-102 and C-103
ANTA FE NEW MEXICO OIL CONSERVATION COMMISSION			Effective 1-1-65
FILE			
U.S.G.S.			State X Fee
LAND OFFICE			5, State Oil & Gas Lease No.
OPERATOR			A-2614
			- Anning Cold
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OF PLUS BACK TO A DIFFERENT HESERVOIR.			
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)			7. Unit Agreement Name
OIL V GAS			South Eunice (Seven
WELL X OTHER-			Rivers, Queen) Unit
Marathon Oil Company			South Eunice(Seven Rivers, Queen) Unit
3. Address of Operator			9. Well No.
P.O. Box 2409, Hobbs New Mexico 88240			405
4. Location of Well			10. Field and Pool, or Wilded
A 660 North 990			South Eunice (Seven Rivers, Queen)
UNIT LETTER A , OC	FEET FROM THE	LINE AND	
East coorday	35 TOWNSHIP 22S	PANGE 36E	NMPN.
THELINE, SECTION	1000		
	15. Elevation (Show whether)	DF, RT, GR, etc.)	12. County
	GL 3476'; 1	KDB 3485'	Lea
Check Ap	ppropriate Box To Indicate N ENTION TO:	-	or Other Data QUENT REPORT OF:
ن	<u></u>	1	<u></u>
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORABILY ASANOON		COMMENCE DRILLING OPNS.	PLUG AND AGANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	casing test and cement JGB (ing Leak and Add Perfs & [X]
		OTHER	Stimulate
67HER	· · · · · · · · · · · · · · · · · · ·		
17. Describe Proposed or Completed Oper work) SEE RULE 1103.	ations (Clearly state all pertinent deta	ils, and give pertinent dates, i	ncluding estimated date of starting any proposed
1. Installed BOP.			
2. Pulled downhole eq	quipment.		
	3678'. Pressured annulus	s. Had leak off.	
4. Set RTTS pkr. at 3647'. Pressured annulus. Held OK.			
5. Filled casing with			
6. Squeezed hole w/10	Oosx. regular cement to	2500 psig.	
7. Drilled out 3675'.	. Pressure tested annulu	ıs. Had leak off.	
8. Squeezed hole w/10	00 sx. regular cement to	o 3800 psig.	
9. Drilled out to 367	75'.Repressure tested a	nnulus to 1600psig.	Dist.
Held OK.			R.P.S.
10. Cleaned out hole to 3787'.			J.C.H.
11. Perfed 5-1/2" casing 3770-76' w/2JSPF (10holes)			Getty Oil Co.
12. Stimulated perfs. 3692-3723',3761-65',& 3770-76' thru Shel			Shell Oil Co.(2)
2-7/8" tubing w/2000gal. 15% NE Acid, 10,000gal. gelled Conti			Continental Oil Co. (2)
ooid () fwan staces.			Gulf Oil Co Hobbs
13 Poron dermhole equipment Cot poelies at 26521			Gulf Oil Co Midland
13. Reran downhole equipment. Set packer at 3653'. 14. Resumed water injection.			COPL
14. Resumed water injec	Etion.		File
13. I hereby certify that the information al	have is true and complete to the best	of my knowledge and belief.	
13. I nereby certify that the information at	/ Land and complete to the best		
SIONED MIL SOL	TITLE Pe	troleum Engineer	мау 7, 1976
	Segman W		MAY 11.1976
• •	Control (Mark Control		DAGE