

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-85

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No. A-2614
7. Unit Agreement Name South Eunice (Seven Rivers, Queen) Unit
8. Farm or Lease Name South Eunice (Seven Rivers, Queen) Unit
9. Well No. 406
10. Field and Pool, or Wildcat South Eunice (Seven Rivers, Queen) Unit
12. County Lea

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator Marathon Oil Company
3. Address of Operator P.O. Box 2409, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER H 1980 FEET FROM THE North LINE AND 990 FEET FROM THE East LINE, SECTION 35 TOWNSHIP 22S RANGE 36E NMPN.
15. Elevation (Show whether DE, RT, GR, etc.) GL 3474'; KDB 3484'

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☒ Perf & Treat Additional Interval in Queen

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Pulled rods and pump.
2. Installed BOP and pulled 2-3/8" tubing.
3. Perforated 5-1/2" casing 3752'-3760' w/1 JSPF (8 holes).
4. Ran RTTS packer on 2-7/8" tubing. Set packer at 3611'.
5. Treated perf interval 3748'-3680' with 2% KCL water pad containing 1500# rock salt and 700# Benzoic acid flakes for divert.
6. Followed pad with 2000 gallons 15% NE acid and 10,000 gallons gelled 2% KCL water and 20,000# sandfrac.
7. Ran 2-3/8" tubing to 3756' with seating nipple at 3757'.
8. Ran 2' X 1 1/2" insert pump on 3/4" rod string.
9. Nippled up wellhead and placed well on production.

Dist.
R.P.S.
J.C.H.
Getty Oil Co.
Shell Oil Co. (2)
Continental Oil Co. (2)
Gulf Oil Co. - Hobbs
Gulf Oil Co. - Midland
COPL
File

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED David J. Stuckler

TITLE Engineer Technician

DATE January 29, 1976

Orig. Signed by
John Sexton

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: Supv.