

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-101 and C-102
Effective 1-1-58

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	5a. Indicate Type of Lease State ☒ Fee ☐
2. Name of Operator Marathon Oil Company	5. State Oil & Gas Lease No. A-2614
3. Address of Operator P.O. Box 2402, Hobbs, New Mexico 88240	7. Unit Agreement Name South Eunice (Seven Rivers, Queen) Unit
4. Location of Well UNIT LETTER J 1980 FEET FROM THE South LINE AND 2310 FEET FROM THE East LINE, SECTION 35 TOWNSHIP 22S RANGE 36E NMPAL.	8. Field, Pool, or Wildcat South Eunice (Seven Rivers, Queen) Unit
15. Elevation (Show whether DF, RT, GR, etc.) GL 3491'; KDB 3502'	9. Well No. 407
	10. Field and Pool, or Wildcat South Eunice (Seven Rivers, Queen) Unit
	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☒ Perforated Treat Additional Interval in Queen

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Pulled rods and pump.
2. Installed BOP and pulled tubing.
3. Perforated 5-1/2" casing 3772'-3778' w/1 JSPF (6 holes).
4. Ran RTTS packer on 2-7/8" tubing. Set packer at 3624'.
5. Treated perms 3700'-3766' and 3772'-78' with 2% KCL water pad containing 3500# rock salt and 1750# of Benzoic acid flakes for divert.
6. Followed pad with 2,000 gallons 15% NE acid and 10,000 gallons of gelled KCL water and 20,000# sandfrac.
7. Ran 2-3/8" tubing to 3782' with seating nipple at 3766'.
8. Ran insert pump and 3/4" rod string.
9. Nipped up wellhead and placed well on production.

Dist.
R.P.S.
J.C.H.
Getty Oil Co.
Shell Oil Co. (2)
Continental Oil Co. (2)
Gulf Oil Co. - Hobbs
Gulf Oil Co. - Midland
COPL
File

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED David D. Strupler TITLE Engineer Technician DATE January 29, 1976
APPROVED BY [Signature] TITLE [Signature] DATE [Signature]
CONDITIONS OF APPROVAL, IF ANY: