

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-101
Effective 1-1-55

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	5a. Indicate Type of Lease State ☒ Fee ☐
2. Name of Operator Marathon Oil Company	5. State Oil & Gas Lease No. A-2614
3. Address of Operator P.O. Box 2409, Hobbs, New Mexico 88240	7. Unit Agreement Name South Eunice (Seven Rivers, Queen) Unit
4. Location of Well UNIT LETTER L 1650 FEET FROM THE South LINE AND 330 FEET FROM THE West LINE, SECTION 36 TOWNSHIP 22S RANGE 36E N.M.P.M.	8. Form or Lease Name South Eunice (Seven Rivers, Queen) Unit
15. Elevation (Show whether DF, RT, GR, etc.) GL 3458'; KDB 3469'	9. Well No. 409
	10. Field or Pool, or Whichever South Eunice (Seven Rivers, Queen)
	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☒ Perf & Treat Additional Interval in Queen

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Pulled rods and pump.
2. Installed BOP and pulled 2-3/8" tubing.
3. Perforated 5-1/2" casing 3732'-3739' w/1 JSPF (7 holes).
4. Ran RTTS packer on 2-7/8" tubing. Set packer at 3565'.
5. Treated perfs 3653'-3728' and 3732'-39' with 2% KCL water pad containing 2000# rock salt and 1000# Benzoic acid flakes for divert.
6. Followed pad with 2000 gallons 15% NE acid and 10,000 gallons KCL water and 20,000# sandfrac.
7. Ran 2-3/8" tubing to 3738' with seating nipple at 3739'
8. Ran 2" X 1 1/2" insert pump on 3/4" rod string.
9. Nippled up wellhead and placed well on production.

Dist.
R.P.S.
J.C.H.
Getty Oil Co.
Shell Oil Co. (2)
Continental Oil Co. (2)
Gulf Oil Co. - Hobbs
Gulf Oil Co. - Midland
COPL
File

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Robert A. Strickler

TITLE Engineer Technician

DATE January 29, 1976

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: