

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIP
(Other instructions
reverse side)

Form approved
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <u>temp. shut-in</u>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR <u>CONOCO INC.</u>	8. FARM OR LEASE NAME <u>Meyer A-29 A/C</u>
3. ADDRESS OF OPERATOR <u>P. O. Box 460, Hobbs, N.M. 88240</u>	9. WELL NO. <u>5</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <u>Unit A</u>	10. FIELD AND POOL, OR WILDCAT <u>Jalmat Yates Gas</u>
14. PERMIT NO. <u>30-025-09186</u>	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>Sec. 29-22S-36E</u>
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <u>990' FNL & 990' FEL</u>	12. COUNTY OR PARISH <u>Lea</u>
	13. STATE <u>NM</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

- ① MIRU on 6/5/86, Tag Fill @ 3321'. Tag top of liner @ 3017'. Set cmt retainer @ 3005'. Pumped 50 sxs class "C" w/2% CaCl₂ below ret.
- ② Spot 25 sxs class "C" on top of ret (3005'-2735'). Spot 100' class "C" plug @ top of salt (1470').
- ③ Ran pkr & isolated csg leak @ 521'. Pumped 300 sxs class "C" w/2% CaCl₂ down csg. Circ. cmt back thru surface csg. Circulated 40 sxs to surface. Closed surface valve and squeezed 75 sxs into formation.
- ④ Cut off csg 3' below ground level, installed P&A marker and rigged down on 6/6/86.



18. I hereby certify that the foregoing is true and correct

SIGNED

Kevin L. Vogel

TITLE Administrative Supervisor

DATE

6-18-86

(This space for Federal or State office use)

APPROVED BY

Chas. E. ...

TITLE

DATE

6-14-86

CONDITIONS OF APPROVAL, IF ANY

*See Instructions on Reverse Side