

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

LC-030133A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well

☒ Other Injection

2. Name of Operator

Conoco Inc.

3. Address and Telephone No.

10 Desta Drive, Ste 100 W, Midland, TX 686-5494

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660 FNL & 660 FEL, Unit letter A, Sect. 29, T22S, R36E

8. Well Name and No.

South Eunice Unit No. 33

9. API Well No.

30-025-09187

10. Field and Pool, or Exploratory Area

Eunice 7 Rvs. Queen

11. County or Parish, State

Lea, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other

Install liner

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completions on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

String out of seal bore w/tension. Reverse out cement. BIH w/2 3/4" bit, 19 jts 2 1/16" tbg 2 3/8" w.s. Jagged aluminum seal bore ext at 3641. 2st csg & liner to 500# - HELD. Do seal bore ext. FC & FS & 1' cmt. Tst to 500# - HELD. POH lost cones. Jagged at 3644. Do cmt from 3644 to 3652. Circ hole clean. 2ag at 3652. Circ hole clean. Do cmt from 3652-53. Co sand to TD 3813. Circ hole clean. BIH w/3" seal nipple anchor assembly & 2 3/8" Plastic coated tbg. Circ hole w/100 BBSLs pkr fluid. Latch on to Magnum GT liner hanger pkr at 3037. 97 jts 2 3/8" IPC tbg 2 x 2 3/8" sub. Tst csg to 500# for 15 min - HELD. RD.

14. I hereby certify that the foregoing is true and correct

Signed

Christine L. Neff

Title

Admin. Assistant

Date

6-28-91

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: