

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Injection Well

2. NAME OF OPERATOR  
CONOCO INC.

3. ADDRESS OF OPERATOR  
P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface Unit I

14. PERMIT NO.  
1980' FSL & 660' FEL

15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
30-025-09194

5. LEASE DESIGNATION AND SERIAL NO.

LC-030133(A)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

South Eunice Unit

8. FARM OR LEASE NAME

South Eunice Unit

9. WELL NO.

43

10. FIELD AND POOL, OR WILDCAT

Eunice 7 Rvrs Queen So.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 29-22S-36E

12. COUNTY OR PARISH 13. STATE

Lea NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- ① MIRU on 11/21/85. Press. test csg to 500 psi, would not hold
- ② Set RBP @ 3592', isolated leak between 1021'-1051'
- ③ Pumped 250 SXS class "C" w/ 2% CaCl<sub>2</sub>. Displaced w/ 22 bbls TFW
- ④ Tag cmt @ 856'. Drill out to 1038'. Circ. sand off RBP & POOH
- ⑤ Circ. 90 bbls pkr fluid & set pkr @ 3592'
- ⑥ Press. test csg to 500 psi for 30 min w/ no leak off.
- ⑦ Rig down on 11/27/85.

RECEIVED FOR RECORD

GARD

JAN 21 1986

CARISPAD, N.M. CONOCO

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Administrative Supervisor

DATE 1-16-86

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

RECEIVED  
JAN 24 1986  
HOLLIS OFFICE