

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
HOBBS, NEW MEXICO 88240

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Inj Well

2. NAME OF OPERATOR
CONOCO INC.

3. ADDRESS OF OPERATOR
P.O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 1660' FEL

14. PERMIT NO.
API # 30-025-09194

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5. LEASE DESIGNATION AND SERIAL NO.

LC-030133A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

S. Eunice Unit

8. FARM OR LEASE NAME

S. Eunice Unit

9. WELL NO.

43

10. FIELD AND POOL, OR WILDCAT

Eunice 7 Rvrs Qn.

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Sec 29-22S-36E

12. COUNTY OR PARISH 13. STATE

Lea

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other) repair csg. leak

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

MIRU. Rel pkr. Set RBP @ 3590' & dump 1 sk sand on top. Isolate csg. leak w/treating
pkr. Poott w/pkr. Set ret 50' above csg leak. If leak is above 1475', pump 16 sxs/100'
hole depth of class "C" cmt w/2% CaCl₂. If leak is below 1475', pump 200 sxs class "C"
cmt w/2% CaCl₂. Flush w/ 1/2 bbl wtr per 100' tbg in hole or 2 bbl wtr per 100'
open csg above hole. WOC. DO ret & cmt. Press test sqz to 500 psi. Resqz if necessary.
Circ sand off RBP & rel. CD to 3828'. Set pkr @ 3589' & place well back on inj.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ken L. Gye

TITLE

Administrative Supervisor

DATE

8/21/85

(This space for Federal or State office use)

APPROVED BY

Don Wood Acting

TITLE

DATE

10-17-85

CONDITIONS OF APPROVAL, IF ANY:

Subject to
Like Approval
by State

*See Instructions on Reverse Side