

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Federal <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LC-030133 A
7. Unit Agreement Name S. Eunice Unit
8. Farm or Lease Name S. Eunice Unit
9. Well No. 43
10. Field and Pool, or Wildcat Eunice 7 Rvrs On.
12. County Lea

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER- **Inj. Well**

2. Name of Operator
CONOCO INC.

3. Address of Operator
P. O. Box 460, Hobbs, N.M. 88240

4. Location of Well
UNIT LETTER **I** **1980** FEET FROM THE **South** LINE AND **1460** FEET FROM
THE **East** LINE, SECTION **29** TOWNSHIP **22S** RANGE **36E** NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

18. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER rep. csg. leak <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRU. Rel pkr. Set RBP @ 3590' & dump 1 sk sand on top. Isolate csg leak w/ treating pkr. Poott w/ pkr. Set cmt ret 50' above leak. If leak is above 1475', pump 16 sxs/100' hole depth of class "C" cmt w/ 2% CaCl₂. If leak is below 1475', pump 200 sxs class "C" cmt w/ 2% CaCl₂. Flush w/ 1/2 bbl wtr per 100' hq. in hole or 2 bbl wtr per 100' open csg above hole. WOC. DO ret & cmt. Press test sqz to 500 psi. Resqz if necessary. Circ sand off RBP & rel. CO to 3828'. Set pkr @ 3589' & place well on inj.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Kevin L. O'Neil* TITLE Administrative Supervisor DATE 8/21/85

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT SUPERVISOR

APPROVED BY _____ TITLE _____ DATE AUG 23 1985

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

AUG 22 1985

OFFICE
HONAS OFFICE